



Zistos Corporation

1736 Church Street

Holbrook, NY 11741

Phone: 631-434-1370 Fax: 631-434-9104

Sales Quotation

Date 7/23/2019 Quote Expires on: 10/21/2019

Questions? Please call 631-434-1370

Quote Number: 002582RK

Foley Police Department
ATTN: Sgt. Eric Holland
200 East Section Avenue
Foley, AL 36535
(251) 943-4431 x240
eholland@foleypolice.org

Line #	Part #	Description	Price	Qty	Extend
1	WS-TSW14	14 ft Tactical Surveillance System including: WalkAbout III 5.6" LCD (WM-5.6-LCD) with detached base (WMX-BASE); 14' Telescoping Pole (T-FNS-14), Right Angle Adapter (R-FNS); Wide Angle, IR Illuminated, Wide Angle IR Illuminated BW Camera (WPC-3.5IR); Audio Module (AAM); two Battery Packs (BAT-2); Universal Harness (WUH); and a single carry case (V-CASE) measuring 53" x 17" x 6. The WalkAbout also includes a Sunshade, Battery Charger, Power Supply and Vehicle Adapter.	\$6,495.00	1	\$6,495.00

UNLESS OTHERWISE NOTED:

Terms: Net 30 days if credit approved, otherwise payment required in advance of shipment.

Standard Shipping: Ground/best way, insured, prepaid and added

Delivery: 4-6 weeks

Sales Tax: Sales tax will be added at time of shipment, if required by state law, unless a sales tax exempt certificate is provided

Sub-Total	\$6,495.00
SHIPPING	\$80.00
Tax	
Total	\$6,575.00

System Contents:

Detached WalkAbout III® - 5.6" LCD Display

WPC-3.5IR - Infrared Illuminated BW Camera

T-FNS-14 - 14' Telescoping Pole

AAM - Audio Module & Two Sets (2) of Earbuds

R-FNS - Right Angle Adapter for pole

BAT-2 - Two (2) NiMH Rechargeable Batteries

WBC - Battery Charger (Power Supply not shown)

T-CASE - Custom Carrying Case

WUH - Universal Chest Harness

SS-WA-5.6 - Sunshade (Not shown)

A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Dual Mode Thermal Camera

View human activity with no illumination through smoke, tear gas and dust with thermal imaging.

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Under-the-Door Camera

Obtain video and audio into rooms with only 1/4" (6mm) door to floor clearance.

Robotic Camera

Receive remote video from a dangerous location with a miniature, extremely rugged, remote controlled, two-wheeled robotic camera.

SYSTEM PART NUMBERS:



1) Add an 'N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



ALTERNATE DISPLAY CONFIGURATIONS



VIDEO MONOCLE



STANDARD WALKABOUT



TANDEM VIEW



WalkAbout III Monitor

Video Monocle

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)	VM LCD: 1.5"D x 2.8"L / 3.4 oz (3.8 x 7.1cm / .1kg) (less eyecup & mount) VM Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg);
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing	Rugged, non-conductive waterproof housing; single watertight connector for both camera and power
Display Size	5.6" (14.2cm) measured diagonally	Effective 1.6" (40cm) diagonal at 39" (1M)
Resolution	640 x 480	320 x 240
Operating Temperature	-4°F to 158°F (-20°C to 70°C)	32°F to 158°F (0°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness	None
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld	On helmet with supplied mount to PVS-14 helmet mounting bracket (PVS helmet mounting not supplied)
Video Format	Auto switches between NTSC (American) or PAL (European)	
Charger	12VDC from either power supply or vehicle adapter	
Batteries	NiMH, 7.2V, 2.7AH	
Discharge Time/ Charge Time	2 hrs. with LEDs off / 2 hrs. when fully discharged	5 hrs. with LEDs off / 2 hrs. when fully discharged
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;	
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)	

Model	WPC-3.5IR
Construction	Submersible enclosure with hard-coated window
Size & Weight	2.5"D x 2.6"L / .36 lbs. (6.4 x 6.6cm / .16kg)
Features	24 IR (invisible) LED, B/W camera, 410K pixels (470K/ PAL), 0.003 lux, 92° FOV

Model	T-FNS-14
Construction	4 Section fiberglass telescoping
Collars	Rugged, break-proof, easy grip, twist collars for each pole section.
Articulation	1 ft (30cm) flexible gooseneck can be flexed into any position
Collapsed/ Extended Length	4ft. with gooseneck folded / 13ft. 11in. (1.2M / 4.2M)
Weight	5.3 lbs. (2.4kg)

Model	T-CASE
Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size	53" x 17" x 6" (135 x 43 x 15cm)
Weight loaded	38 lbs. (17.3kg)

Audio

Model	AAM Audio Module
Construction	Weatherproof enclosure; fits between pole and camera
Size & Weight	1.5"D x 3.25"L / .22 lbs. (3.8 x 8.3cm / .10kg)
Features	Internal microphone with high gain amplifier; earbuds with volume control