



WARD
INTERNATIONAL TRUCKS

Thursday, March 31, 2022

City of Foley
Darrell Russell, Public Works Director
120 E. Orchid Street
P.O. Box 1750
Foley AL 36535

RE: QUOTES ON FOLLOWING (1) 2022 INTERNATIONAL CV515 SFA 4X2 CONVENTIONAL DAY CAB CHASSIS WITH 11' DROP SIDE DUMP BODY (2) 2022 INTERNATIONAL CV515 SFA 4X4 CREW CAB CHASSIS WITH 11' DROP SIDE DUMP BODY and (3) 2022 INTERNATIONAL CV515 SFA 4X2 CONVENTIONAL DAY CAB WITH 14' HIGH SIDE DUMP BODY

Darrell:

Per your request we offer the following:

3011 (1) 2022 INTERNATIONAL CV515 SFA 4X2 CONVENTIONAL DAYCAB CHASSIS WITH 11' DROP SIDE DUMP BODY @ **\$71,785.00** FOB Foley AL. (VIN NH622095 or equal)

3011 (2) 2022 INTERNATIONAL CV515 SFA 4X4 CREW CAB CHASSIS WITH 11' DROP SIDE DUMP BODY @ **\$80,760.00** FOB Foley AL. (VIN NH622088 or equal)

3013 (3) 2022 INTERNATIONAL CV515 SFA 4X2 CONVENTIONAL DAY CAB CHASSIS WITH 14' HIGH SIDE DUMP BODY @ **\$75,350.00** FOB Foley AL. (VIN NH622096 or equal)

Detailed chassis specifications for each configuration are attached for your review. Chassis VIN NH622095 and NH622088 are IN STOCK and available for immediate delivery. Chassis VIN NH622096 has an estimated build date of 04-13-22. We expect this chassis to be delivered to us in May.

Body for item 1 & 2 will be Knapheide (or equal) 11' dump body for 84" CA CV515 chassis. Includes double acting tailgate, drop sides, board pockets, rear hitch with combo draw bar, electric/hydraulic double acting hoist (power up and power down), back up alarm, mud flaps, trailer plug, corner strobes and ¼ cab shield. Lead time for delivery of Knapheide body is estimated at 24 weeks after receipt of order. Body installation by Truck Equipment Sales, Mobile AL.

2101 Perimeter Road
(I-10/Michigan Avenue)
Mobile, AL 36615
(800) 476-6841 Toll Free
(251) 433-5616 Office
(251) 433-5617 Fax
www.wardintltrucks.com

Page 2

City of Foley

March 31, 2000

Body for item 3 will be custom built 14' flatbed dump body for 108" CA CV515 chassis. Includes 14' flatbed with 48" tall headboard and 40" solid fixed side walls. Barn door rear gate. Black paint, mud flaps, LED marker lights and corner strobes. Rear dump hitch with 7-way plug and D-rings. Hoist will be Venco VC628-ES electric over hydraulic. Body installation by Truck Equipment Sales, Mobile AL.

Pricing per Navistar/ Sourcewell Contract #060920-NVS. Please reference this contract number on your purchase order. Price includes Sourcewell approved chassis commodity surcharges from International of \$2,500.00 for CV series chassis and \$180.00 for Continental or Hankook tires.

Please let me know if you need additional information. Thank you for the opportunity.

Sincerely,

Howard Clotfelter
Ward International Trucks

Prepared For:
Foley, City Of
Darrell Russell
407 E Laurel Ave.
Foley, AL 36535-2619
(251)943 - 1545

FOR ST CNSTR (3011)

Presented By:
WARD INT'L TRUCKS
Howard M Clotfelter
2101 PERIMETER RD
MOBILE AL 36615 -
(251)433-5616

Model Profile
2022 CV515 SFA (CV515)

AXLE CONFIG: 4X2
MISSION: Requested GVWR: 19500, Calc. GVWR: 19500, Calc. GCWR: 26000
DIMENSION: Wheelbase: 165.00, CA: 83.80, Axle to Frame: 63.00
ENGINE, DIESEL: {International 6.6} EPA 2021, 350HP @ 2700 RPM, 700 lb-ft Torque @ 1600 RPM, 2900 RPM Governed Speed, 350 Peak HP (Max)
TRANSMISSION, AUTOMATIC: {Allison 1700 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Park Pawl, with 19,500-lb GVW and 26,000-lb GCW Max, On/Off Highway
AXLE, FRONT NON-DRIVING: {Dana Spicer D-800N} I-Beam Type, 7,000-lb Capacity
AXLE, REAR, SINGLE: {Dana Spicer S14-110} Single Reduction, 13,500-lb Capacity, 190 Wheel Ends Gear Ratio: 4.10
CAB: Conventional, Day Cab
TIRE, FRONT: (2) 225/70R19.5 Load Range G HYBRID HS3 (CONTINENTAL), 649 rev/mile, 87 MPH, All-Position
TIRE, REAR: (4) 225/70R19.5 Load Range G HYBRID HD3 (CONTINENTAL), 647 rev/mile, 87 MPH, Drive
SUSPENSION, REAR, SINGLE: 13,500-lb Capacity, Vari-Rate Springs
PAINT: Cab schematic 100CX
Location 1: 9219, Winter White (Std)
Chassis schematic N/A

(1) 2022 INTERNATIONAL CV 515 SFA 4X2 CONVENTIONAL CAB CHASSIS (VIN NH622095 or equal)

Code	Description	F/R Wt (lbs)	Tot Wt (lbs)
CV51500	Base Chassis, Model CV515 SFA with 165.00 Wheelbase, 83.80 CA, and 63.00 Axle to Frame.	4671/2886	7557

AXLE CONFIGURATION

1ANA	AXLE CONFIGURATION {Navistar} 4x2	0/0	0
	<u>Notes</u> : Pricing may change if axle configuration is changed.		

ENGINE

12GAG	ENGINE, DIESEL {International 6.6} EPA 2021, 350HP @ 2700 RPM, 700 lb-ft Torque @ 1600 RPM, 2900 RPM Governed Speed, 350 Peak HP (Max)	0/0	0
	<u>Includes</u> : GLOW PLUG Automatic with Indicator Light : OIL FILTER, ENGINE Spin-On Type		
12XCU	CARB EMISSION WARR COMPLIANCE for International 6.6 Engines	0/0	0
12WZB	CARB IDLE COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood	0/0	0
12VJD	EMISSION, CALENDAR YEAR {International 6.6} EPA, OBD and GHG Certified for Calendar Year 2022	0/0	0
12XZD	RADIATOR Aluminum, 3-Row, Down Flow, Front to Back System, 730 SqIn Louvered, with 578 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler	0/0	0
12TTM	FAN DRIVE Viscous Type, Screw On, Rear Tether, Electronically Controlled	0/0	0
12VGC	AIR CLEANER Single Element, with Water Separator	0/0	0
12WUU	GOVERNOR Electronic Road Speed Type; with 75 MPH Default	0/0	0
12WGG	THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic Controlled, On/Off Switch Mounted on Dash, with Steering Wheel Button Control	0/0	0

TRANSMISSION

13AWY	TRANSMISSION, AUTOMATIC {Allison 1700 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Park Pawl, with 19,500-lb GVW and 26,000-lb GCW Max, On/Off Highway	0/0	0
13WVV	NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released	0/0	0
13XAK	PTO LOCATION Customer Intends to Install PTO at Right Side of Transmission	0/0	0
13WYY	SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming	0/0	0

REAR AXLES, SUSPENSIONS

14ACW	AXLE, REAR, SINGLE {Dana Spicer S14-110} Single Reduction, 13,500-lb Capacity, 190 Wheel Ends . Gear Ratio: 4.10	0/0	0
14SAC	SUSPENSION, REAR, SINGLE 13,500-lb Capacity, Vari-Rate Springs	0/60	60
14WMN	AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 1 thru 29.99 Pints	0/0	0
14WAP	SHOCK ABSORBERS, REAR (2)	0/50	50

FRONT AXLES

2AJK	AXLE, FRONT NON-DRIVING {Dana Spicer D-800N} I-Beam Type, 7,000-lb Capacity	0/0	0
------	---	-----	---

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
FRONT SUSPENSIONS			
3AGN	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 7,000-lb Capacity, with Shock Absorbers	24/0	24
CABS, COWLS, BODIES			
16030	CAB Conventional, Day Cab <u>Includes</u> : CAB DOOR LOCKS Power Door Locks All Doors : DOME LIGHT, CAB with OFF/DOOR/ON Settings; Located in Overhead Console : READING LIGHT, CAB Located in Overhead Console : STEP (2) One Per Door : STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door	0/0	0
16XCP	AIR BAG, FRONT, DRIVER SIDE	0/0	0
16XCR	AIR BAG, FRONT, PASSENGER SIDE	0/0	0
16XDE	AIR BAG, SIDE, DRIVER Seat Mounted, Outboard Side-Impact Airbag	0/0	0
16XDG	AIR BAG, SIDE, PASSENGER Seat Mounted, Outboard Side-Impact Airbag	0/0	0
16XDH	AIR BAG, SIDE CURTAIN Roof Mounted, for Front and Rear Outboard Seating Positions for Driver and Passenger Sides	0/0	0
16XZA	AIR CONDITIONER with Heater, Single Zone	0/0	0
16VKK	CAB INTERIOR TRIM Diamond, for Day Cab	0/0	0
16CEM	COLOR, INTERIOR Dark Ash	0/0	0
16BAN	DOOR HANDLE, EXTERIOR Bright Finish	0/0	0
16HLY	GAUGE CLUSTER English Speedometer, Includes English Odometer; Includes 4.2" Color Display with Personalization, Warning Messages and Vehicle Information	0/0	0
16BBA	GLASS, ALL WINDOWS Solar Absorbing, Tint	0/0	0
16XAL	KEYLESS ENTRY SYSTEM REMOTE with Panic Alarm and Horn Beep Lock Confirmation, Includes Two Key Fob Transmitters	0/0	0
16ACC	MIRROR, INSIDE REAR VIEW with Automatic Dimming	0/0	0
16SPT	MIRRORS (2) Manual Folding and Extending, Power Adjust, Heated, Turn Signal Indicator Located in Mirror, Bright Heads and Arms, for 96" Load Width	5/0	5
16KVU	SEAT, DRIVER High Back with Integral Headrest, 10-Way Power Adjustable, Cloth, Manual Adjust Lumbar	0/0	0
16LVP	SEAT, TWO-MAN PASSENGER High Back with Integral Headrest in Outboard Position, Center Fold-Down Armrest with Storage, Cloth, with Recline	0/0	0
16XCS	SUN VISOR, INTERIOR with Illuminated Mirror for Driver and Passenger Sides	0/0	0
16WAK	WINDOW, POWER (2) in Left and Right Doors	0/0	0
FRAMES			
1CGH	FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield), Straight Top Flange with Contoured Bottom, Height Transitions from 7.375" (187.325mm) to 9.125" (231.775mm) to 7.625" (193.675mm); Width: 3.079" (78.21mm); Thickness: 0.3125" (7.94mm); 383.3" (9735.8mm) Max OAL	28/78	106
1LNZ	BUMPER, FRONT Contoured, Steel, Chrome Plated, for CV and RE Bus	0/0	0
1570	TOW HOOK, FRONT (2) Frame Mounted	13/-1	12
1WND	AF RANGE 50" (128cm) Through and Including 75" (190cm)	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
1WEB	WHEELBASE RANGE 128" (325cm) Through and Including 183" (465cm)	0/0	0
BRAKES			
4240	BRAKE SYSTEM, HYDRAULIC (Bosch) Split System, with Four Channel ABS, Traction Control, Electronic Stability Control, Hydromax Brake Booster with High Speed Master Cylinder and Trailer Sway Control	0/0	0
4GBJ	BRAKE, PARKING (Bosch) DSSA Type, 12" x 3"; for Hydraulic Brake Chassis; Foot Operated in Cab; Differential Mounted	0/0	0
4XCU	BRAKES, FRONT (Meritor Quadraulic) Hydraulic Disc Type, with Four 64mm Diameter Pistons, 8,000-lb Capacity	0/0	0
4EVD	DUST SHIELDS, FRONT BRAKE for Hydraulic Brakes	0/0	0
4XCV	BRAKES, REAR (Meritor Quadraulic) Hydraulic Disc Type, with Four 64mm Diameter Pistons, 15,500-lb Capacity per Axle	0/0	0
4EVE	DUST SHIELDS, REAR BRAKE for Hydraulic Brakes	0/0	0
STEERING			
5PSS	STEERING GEAR (Bosch S2 8014 Plus) Power	0/0	0
5708	STEERING COLUMN Tilling	0/0	0
5CBH	STEERING WHEEL 4-Spoke; 15" Dia., Black, Leather Wrapped	0/0	0
DRIVELINES			
6DGA	DRIVELINE SYSTEM (Dana Spicer) SPL100, for 4x2/6x2	0/0	0
EXHAUST SYSTEMS			
7BLL	EXHAUST SYSTEM Horizontal, Frame Mounted Right Side, Under Rail, for Single Exhaust	0/0	0
7SDS	ENGINE EXHAUST BRAKE for International 6.6 Engine	0/0	0
7XAA	MANUAL REGEN Capability	0/0	0
ELECTRICAL SYSTEMS			
8002	ELECTRICAL SYSTEM 12-Volt for CV Model	0/0	0
	<u>Includes</u> : HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : PARKING LIGHT PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : TURN SIGNALS, FRONT Includes Reflectors and Solid State Flashers; Flush Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature, Integral with Turn Signal Lever		
8GJA	ALTERNATOR (Denso SC2) Brush Type, 12 Volt, 150 Amp Capacity	0/0	0
8VVB	BATTERY BOX Steel, with Plastic Cover, 2 Battery Capacity, Parallel to Rail, 28" Wide, Mounted Left Side Under Cab	0/0	0
8MVZ	BATTERY SYSTEM (VARTA) Maintenance-Free, (2) 12-Volt 1100CCA Total, Top Threaded Stud	0/0	0
8HXV	BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Crew Cab at Left Frame; Includes One Sealed Connector for Separate Ground/Backup/Left and Right Hand Turn, Left and Right Hand Tail/Stop/Accessory Power and Combined for Left and Right Hand Stop/Turn	3/1	4
8XJV	CLEARANCE/MARKER LIGHTS (5) Amber LED Lights, Flush Mounted on Cab	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
8RNS	COMPACT DISC PLAYER with MP3	2/0	2
8XJM	HEADLIGHTS Halogen, Composite Aero Design, Chrome Trim Bezel, with Daytime Running Lights	0/0	0
8VAY	HORN, ELECTRIC Disc Style	0/0	0
8RNR	RADIO AM/FM/Bluetooth/USB Input/Auxiliary Input/SD Card Slot, with 8" Color Touch Panel Display, Voice Activated Technology, Satellite Radio Compatible	0/0	0
8RNU	SPEAKERS (6)	2/0	2
8XJW	STARTING MOTOR 12 Volt	0/0	0
8TUL	STOP, TURN, TAIL & B/U LIGHTS Multi-Function, Sealed, Incandescent Stop, Turn and Tail Lights, Backup Lights with Rear Reflex Reflector, Includes License Plate Light	0/0	0
8XJP	SWITCH, AUXILIARY 1 to 4 Latching Switches with 30-Amp Fuses	0/0	0

FRONT END

9WAY	FRONT END Tilting, Fiberglass, with Three Piece Construction	0/0	0
9WAC	BUG SCREEN Mounted Behind Grille	0/0	0
9WBN	FENDER EXTENSIONS Painted	0/0	0
9HCG	GRILLE Chrome, with Chrome Headlight Bezels	0/0	0
9AAB	LOGOS EXTERIOR Model Badges	0/0	0

SPEEDOMETER, TOOLS, MISC

10JPA	CUSTOMER IDENTITY for Sourcewell	0/0	0
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
10SLV	PROMOTIONAL PACKAGE Government Silver Package	0/0	0
10XAW	GVWR WEIGHT CLASSIFICATION Class 5 (16,001-19,500 lbs)	0/0	0
10WGE	SPECIAL RATING, GVWR Limited to 19,500-lb GVWR	0/0	0

FUEL TANKS

15SZN	FUEL TANK Top Draw, Plastic, Rectangular, 17" Tank Depth, 40 US Gal (151L), Includes Auxiliary Draw Port and Fuel Filler Assembly, Mounted Between Frame Rails and Behind Rear Axle	0/0	0
15WDZ	DEF TANK 6.75 US Gal (26L) Capacity, Frame Mounted Outside Right Rail, Under Cab	0/0	0

WHEELS, TIRES - FRONT

27DTX	WHEELS, FRONT {Accuride 50180} DISC; 19.5x6.75 Rims, Powder Coat Steel, 4-Hand Hole, 8-Stud, 275mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
7779445433	(2) TIRE, FRONT 225/70R19.5 Load Range G HYBRID HS3 (CONTINENTAL), 649 rev/mile, 87 MPH, All-Position	0/0	0

WHEELS, TIRES - REAR

28DTX	WHEELS, REAR {Accuride 50180} DUAL DISC; 19.5x6.75 Rims, Powder Coat Steel, 4-Hand Hole, 8-Stud, 275mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
-------	--	-----	---

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
7779445428	(4) TIRE, REAR 225/70R19.5 Load Range G HYBRID HD3 (CONTINENTAL), 647 rev/mile, 87 MPH, Drive	0/16	16
	Cab schematic 100CX		
	Location 1: 9219, Winter White (Std)		
	Chassis schematic N/A		
	Services Section:		

WARRANTY

40131	WARRANTY Standard for CV515, Effective with Vehicles Built December 3, 2018 or Later, CTS-3000A	0/0	0
	Total Component Weight:	4748/3090	7838
Body/Allied Equipment			
<u>Code</u>	<u>Description</u>	<u>F/R Wt</u>	<u>Tot Wt</u>
Goods Purchased			
<u>Code</u>	<u>Description</u>	<u>F/R Wt</u>	<u>Tot Wt</u>
	Knapheide 11' drop side dump body. Installation by Truck Equipment Sales, Mobile AL.	0/0	0
	Local Post Build	0/0	0
	Raw Materials Surcharge	0/0	0
	Total Goods Purchased:	0/0	0

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.

Prepared For:
Foley, City Of
Darrell Russell
407 E Laurel Ave.
Foley, AL 36535-2619
(251)943 - 1545

FOR ST CNSTR (3011)

Presented By:
WARD INT'L TRUCKS
Howard M Clotfelter
2101 PERIMETER RD
MOBILE AL 36615 -
(251)433-5616

Model Profile
2022 CV515 SFA (CV515)

AXLE CONFIG: 4X4
MISSION: Requested GVWR: 19500, Calc. GVWR: 19500, Calc. GCWR: 26000
DIMENSION: Wheelbase: 199.00, CA: 83.80, Axle to Frame: 63.00
ENGINE, DIESEL: {International 6.6} EPA 2021, 350HP @ 2700 RPM, 700 lb-ft Torque @ 1600 RPM, 2900 RPM Governed Speed, 350 Peak HP (Max)
TRANSMISSION, AUTOMATIC: {Allison 1700 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Park Pawl, with 19,500-lb GVW and 26,000-lb GCW Max, On/Off Highway
AXLE, FRONT DRIVING: {Dana Spicer 60-256} Single Reduction, 7,500-lb Capacity, with Hub Piloted Wheel Mounting
AXLE, REAR, SINGLE: {Dana Spicer S14-110} Single Reduction, 13,500-lb Capacity, 190 Wheel Ends Gear Ratio: 4.30
CAB: Conventional 6-Man Crew Cab
TIRE, FRONT: (2) 225/70R19.5 Load Range H CROSSTRAC HA3 (CONTINENTAL), 649 rev/mile, 75 MPH, All-Position
TIRE, REAR: (4) 225/70R19.5 Load Range G HYBRID HD3 (CONTINENTAL), 647 rev/mile, 87 MPH, Drive
SUSPENSION, REAR, SINGLE: 15,500-lb Capacity, Vari-Rate Springs
PAINT: Cab schematic 100CX
Location 1: 9219, Winter White (Std)
Chassis schematic N/A

(2) 2022 INTERNATIONAL CV 515 SFA 4X4 CREW CAB CHASSIS (VIN NH622088 or equal)

Code	Description	F/R Wt (lbs)	Tot Wt (lbs)
CV51500	Base Chassis, Model CV515 SFA with 199.00 Wheelbase, 83.80 CA, and 63.00 Axle to Frame.	4671/2886	7557

AXLE CONFIGURATION

1ANB	AXLE CONFIGURATION {Navistar} 4x4	0/0	0
	<u>Notes</u> : Pricing may change if axle configuration is changed.		

ENGINE

12GAG	ENGINE, DIESEL {International 6.6} EPA 2021, 350HP @ 2700 RPM, 700 lb-ft Torque @ 1600 RPM, 2900 RPM Governed Speed, 350 Peak HP (Max)	0/0	0
	<u>Includes</u> : GLOW PLUG Automatic with Indicator Light : OIL FILTER, ENGINE Spin-On Type		
12XCU	CARB EMISSION WARR COMPLIANCE for International 6.6 Engines	0/0	0
12WZB	CARB IDLE COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood	0/0	0
12VJD	EMISSION, CALENDAR YEAR {International 6.6} EPA, OBD and GHG Certified for Calendar Year 2022	0/0	0
12XZD	RADIATOR Aluminum, 3-Row, Down Flow, Front to Back System, 730 SqIn Louvered, with 578 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler	0/0	0
12TTM	FAN DRIVE Viscous Type, Screw On, Rear Tether, Electronically Controlled	0/0	0
12VGC	AIR CLEANER Single Element, with Water Separator	0/0	0
12WUU	GOVERNOR Electronic Road Speed Type; with 75 MPH Default	0/0	0
12WGG	THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic Controlled, On/Off Switch Mounted on Dash, with Steering Wheel Button Control	0/0	0

TRANSMISSION

13AWY	TRANSMISSION, AUTOMATIC {Allison 1700 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Park Pawl, with 19,500-lb GVW and 26,000-lb GCW Max, On/Off Highway	0/0	0
13WVV	NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released	0/0	0
13XAK	PTO LOCATION Customer Intends to Install PTO at Right Side of Transmission	0/0	0
13WYY	SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming	0/0	0
13TLP	TRANSFER CASE {Meritor MTC-3203} 2-Speed, Gear Drive, 3,000 lb-ft Torque Rating, Less PTO Provision, Electric Shift Control	159/29	188
	<u>Notes</u> : Transfer Case Includes 40W Synthetic Lube		

REAR AXLES, SUSPENSIONS

14ACW	AXLE, REAR, SINGLE {Dana Spicer S14-110} Single Reduction, 13,500-lb Capacity, 190 Wheel Ends . Gear Ratio: 4.30	0/0	0
14SAE	SUSPENSION, REAR, SINGLE 15,500-lb Capacity, Vari-Rate Springs	0/41	41
14WMN	AXLE, REAR, LUBE {Emgard FE-75W-90} Synthetic Oil; 1 thru 29.99 Pints	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
14WAP	SHOCK ABSORBERS, REAR (2)	0/50	50
FRONT AXLES			
2EWA	AXLE, FRONT DRIVING (Dana Spicer 60-256) Single Reduction, 7,500-lb Capacity, with Hub Piloted Wheel Mounting	155/0	155
2WLC	AXLE, FRONT DRIVING, LUBE (EmGard FE-75W-90) Synthetic Oil; 1 thru 29.99 Pints	0/0	0
FRONT SUSPENSIONS			
3AJN	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 7,500-lb Capacity, with Shock Absorbers	31/0	31
CABS, COWLS, BODIES			
16196	CAB Conventional 6-Man Crew Cab	336/230	566
	<u>Includes</u> : CAB DOOR LOCKS Power Door Locks All Doors : DOME LIGHT, CAB with OFF/DOOR/ON Settings; Located in Overhead Console : READING LIGHT, CAB Located in Overhead Console : STEP (4) One Step Per Door : STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door		
16XCP	AIR BAG, FRONT, DRIVER SIDE	0/0	0
16XCR	AIR BAG, FRONT, PASSENGER SIDE	0/0	0
16XDE	AIR BAG, SIDE, DRIVER Seat Mounted, Outboard Side-Impact Airbag	0/0	0
16XDG	AIR BAG, SIDE, PASSENGER Seat Mounted, Outboard Side-Impact Airbag	0/0	0
16XDH	AIR BAG, SIDE CURTAIN Roof Mounted, for Front and Rear Outboard Seating Positions for Driver and Passenger Sides	0/0	0
16XZA	AIR CONDITIONER with Heater, Single Zone	0/0	0
16VKM	CAB INTERIOR TRIM Diamond, for Crew Cab	0/0	0
16CEM	COLOR, INTERIOR Dark Ash	0/0	0
16BAN	DOOR HANDLE, EXTERIOR Bright Finish	0/0	0
16HLY	GAUGE CLUSTER English Speedometer, Includes English Odometer; Includes 4.2" Color Display with Personalization, Warning Messages and Vehicle Information	0/0	0
16BBA	GLASS, ALL WINDOWS Solar Absorbing, Tint	0/0	0
16XAL	KEYLESS ENTRY SYSTEM REMOTE with Panic Alarm and Horn Beep Lock Confirmation, Includes Two Key Fob Transmitters	0/0	0
16ACC	MIRROR, INSIDE REAR VIEW with Automatic Dimming	0/0	0
16SPT	MIRRORS (2) Manual Folding and Extending, Power Adjust, Heated, Turn Signal Indicator Located in Mirror, Bright Heads and Arms, for 96" Load Width	5/0	5
16KVU	SEAT, DRIVER High Back with Integral Headrest, 10-Way Power Adjustable, Cloth, Manual Adjust Lumbar	0/0	0
16LVP	SEAT, TWO-MAN PASSENGER High Back with Integral Headrest in Outboard Position, Center Fold-Down Armrest with Storage, Cloth, with Recline	0/0	0
16KZB	SEAT, REAR BENCH, Cloth	0/0	0
16XCS	SUN VISOR, INTERIOR with Illuminated Mirror for Driver and Passenger Sides	0/0	0
16XCT	WINDOW, POWER (4) in Left and Right Doors, Front and Rear	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
FRAMES			
1CGH	FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield), Straight Top Flange with Contoured Bottom, Height Transitions from 7.375" (187.325mm) to 9.125" (231.775mm) to 7.625" (193.675mm); Width: 3.079" (78.21mm); Thickness: 0.3125" (7.94mm); 383.3" (9735.8mm) Max OAL	81/121	202
1LNZ	BUMPER, FRONT Contoured, Steel, Chrome Plated, for CV and RE Bus	0/0	0
1AMM	SKID PLATE Steel, Frame Mounted, Protects the Transfer Case from the Ground	50/14	64
1570	TOW HOOK, FRONT (2) Frame Mounted	13/-1	12
1WND	AF RANGE 50" (128cm) Through and Including 75" (190cm)	0/0	0
1WEC	WHEELBASE RANGE 185" (470cm) Through and Including 236" (600cm)	10/30	40
BRAKES			
4240	BRAKE SYSTEM, HYDRAULIC {Bosch} Split System, with Four Channel ABS, Traction Control, Electronic Stability Control, Hydromax Brake Booster with High Speed Master Cylinder and Trailer Sway Control	0/0	0
4GBJ	BRAKE, PARKING {Bosch} DSSA Type, 12" x 3"; for Hydraulic Brake Chassis; Foot Operated in Cab; Differential Mounted	0/0	0
4XCU	BRAKES, FRONT {Meritor Quadraulic} Hydraulic Disc Type, with Four 64mm Diameter Pistons, 8,000-lb Capacity	0/0	0
4EVD	DUST SHIELDS, FRONT BRAKE for Hydraulic Brakes	0/0	0
4XCV	BRAKES, REAR {Meritor Quadraulic} Hydraulic Disc Type, with Four 64mm Diameter Pistons, 15,500-lb Capacity per Axle	0/0	0
4EVE	DUST SHIELDS, REAR BRAKE for Hydraulic Brakes	0/0	0
STEERING			
5PSS	STEERING GEAR {Bosch S2 8014 Plus} Power	0/0	0
5708	STEERING COLUMN Tilting	0/0	0
5CBH	STEERING WHEEL 4-Spoke; 15" Dia., Black, Leather Wrapped	0/0	0
DRIVELINES			
6DHD	DRIVELINE SYSTEM {Dana Spicer} SPL100 Main Driveline, Direct Mount Transfer Case to Transmission, SPL70 Driveline to Front Axle, for 4x4	0/2	2
EXHAUST SYSTEMS			
7BLL	EXHAUST SYSTEM Horizontal, Frame Mounted Right Side, Under Rail, for Single Exhaust	0/0	0
7SDS	ENGINE EXHAUST BRAKE for International 6.6 Engine	0/0	0
7XAA	MANUAL REGEN Capability	0/0	0
ELECTRICAL SYSTEMS			
8002	ELECTRICAL SYSTEM 12-Volt for CV Model	0/0	0
	Includes : HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : PARKING LIGHT PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : TURN SIGNALS, FRONT Includes Reflectors and Solid State Flashers; Flush Mounted		

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
	: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature, Integral with Turn Signal Lever		
8GJA	ALTERNATOR (Denso SC2) Brush Type, 12 Volt, 150 Amp Capacity	0/0	0
8VVB	BATTERY BOX Steel, with Plastic Cover, 2 Battery Capacity, Parallel to Rail, 28" Wide, Mounted Left Side Under Cab	0/0	0
8MVZ	BATTERY SYSTEM (VARTA) Maintenance-Free, (2) 12-Volt 1100CCA Total, Top Threaded Stud	0/0	0
8HXV	BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Crew Cab at Left Frame; Includes One Sealed Connector for Separate Ground/Backup/Left and Right Hand Turn, Left and Right Hand Tail/Stop/Accessory Power and Combined for Left and Right Hand Stop/Turn	3/1	4
8XJV	CLEARANCE/MARKER LIGHTS (5) Amber LED Lights, Flush Mounted on Cab	0/0	0
8RNS	COMPACT DISC PLAYER with MP3	2/0	2
8XJM	HEADLIGHTS Halogen, Composite Aero Design, Chrome Trim Bezel, with Daytime Running Lights	0/0	0
8VAY	HORN, ELECTRIC Disc Style	0/0	0
8RNW	RADIO AM/FM/Bluetooth/USB Input/Auxiliary Input/SD Card Slot, with 8" Color Touch Panel Display, Voice Activated Technology	0/0	0
8RNU	SPEAKERS (6)	2/0	2
8XJW	STARTING MOTOR 12 Volt	0/0	0
8TUL	STOP, TURN, TAIL & B/U LIGHTS Multi-Function, Sealed, Incandescent Stop, Turn and Tail Lights, Backup Lights with Rear Reflex Reflector, Includes License Plate Light	0/0	0
8XJP	SWITCH, AUXILIARY 1 to 4 Latching Switches with 30-Amp Fuses	0/0	0

FRONT END

9WAY	FRONT END Tilting, Fiberglass, with Three Piece Construction	0/0	0
9WAC	BUG SCREEN Mounted Behind Grille	0/0	0
9WBN	FENDER EXTENSIONS Painted	0/0	0
9HCG	GRILLE Chrome, with Chrome Headlight Bezels	0/0	0
9AAB	LOGOS EXTERIOR Model Badges	0/0	0

SPEEDOMETER, TOOLS, MISC

10JPA	CUSTOMER IDENTITY for Sourcewell	0/0	0
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
10SLV	PROMOTIONAL PACKAGE Government Silver Package	0/0	0
10XAW	GVWR WEIGHT CLASSIFICATION Class 5 (16,001-19,500 lbs)	0/0	0
10WGE	SPECIAL RATING, GVWR Limited to 19,500-lb GVWR	0/0	0

FUEL TANKS

15SZN	FUEL TANK Top Draw, Plastic, Rectangular, 17" Tank Depth, 40 US Gal (151L), Includes Auxiliary Draw Port and Fuel Filler Assembly, Mounted Between Frame Rails and Behind Rear Axle	0/0	0
15WDZ	DEF TANK 6.75 US Gal (26L) Capacity, Frame Mounted Outside Right Rail, Under Cab	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
WHEELS, TIRES - FRONT			
27DVT	WHEELS, FRONT (Alcoa 76543) DISC; 19.5x6.75 Rims, Mirror Polish Aluminum, 8-Stud, 275mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	-62/0	-62
7789445436	(2) TIRE, FRONT 225/70R19.5 Load Range H CROSSTRAC HA3 (CONTINENTAL), 649 rev/mile, 75 MPH, All-Position	10/0	10

WHEELS, TIRES - REAR

28DVT	WHEELS, REAR (Alcoa 76543) DUAL DISC; 19.5" Mirror Polish Aluminum Outer Wheel and Steel Inner Wheel, 8-Stud (275MM BC) Hub Piloted, Flanged Nut, Metric Mount, 6.75 Rims; with Steel Hubs	0/-125	-125
7779445428	(4) TIRE, REAR 225/70R19.5 Load Range G HYBRID HD3 (CONTINENTAL), 647 rev/mile, 87 MPH, Drive	0/16	16

WHEELS MISC OPTIONS

29PBZ	COATING IDENTITY, FRONT WHEELS {Alcoa Dura-Bright XBR/EVO} Disc Front Wheels, Aluminum, with Vendor Applied Treatment, Not for Wide Base	0/0	0
29PBY	COATING IDENTITY, REAR WHEELS {Alcoa Dura-Bright XBR/EVO} Disc Rear Wheels, Aluminum, with Vendor Applied Treatment, Not for Super Single/Wide Base	0/0	0
	Cab schematic 100CX		
	Location 1: 9219, Winter White (Std)		
	Chassis schematic N/A		

Services Section:**WARRANTY**

40131	WARRANTY Standard for CV515, Effective with Vehicles Built December 3, 2018 or Later, CTS-3000A	0/0	0
-------	---	-----	---

Total Component Weight:

5466/3294 8760

Body/Allied Equipment

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u>	<u>Tot Wt</u>
Goods Purchased			
<u>Code</u>	<u>Description</u>	<u>F/R Wt</u>	<u>Tot Wt</u>
	Knapheide 11' drop side dump body. Installation by Truck Equipment Sales, Mobile AL.	0/0	0
	Local Post Build	0/0	0
	Raw Materials Surcharge	0/0	0
	Total Goods Purchased:	0/0	0

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.

Prepared For:
Foley, City Of
Darrell Russell
407 E Laurel Ave.
Foley, AL 36535-2619
(251)943 - 1545

FOR ST. SDWLKS (3013)

Presented By:
WARD INT'L TRUCKS
Howard M Clotfelter
2101 PERIMETER RD
MOBILE AL 36615 -
(251)433-5616

Model Profile
2022 CV515 SFA (CV515)

AXLE CONFIG:	4X2
MISSION:	Requested GVWR: 19500. Calc. GVWR: 19500. Calc. GCWR: 26000
DIMENSION:	Wheelbase: 189.00, CA: 107.80, Axle to Frame: 63.00
ENGINE, DIESEL:	{International 6.6} EPA 2021, 350HP @ 2700 RPM, 700 lb-ft Torque @ 1600 RPM, 2900 RPM Governed Speed, 350 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 1700 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Park Pawl, with 19,500-lb GVW and 26,000-lb GCW Max, On/Off Highway
AXLE, FRONT NON-DRIVING:	{Dana Spicer D-800N} I-Beam Type, 7,000-lb Capacity
AXLE, REAR, SINGLE:	{Dana Spicer S14-110} Single Reduction, 13,500-lb Capacity, 190 Wheel Ends Gear Ratio: 4.10
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 225/70R19.5 Load Range G HYBRID HS3 (CONTINENTAL), 649 rev/mile, 87 MPH, All-Position
TIRE, REAR:	(4) 225/70R19.5 Load Range G HYBRID HD3 (CONTINENTAL), 647 rev/mile, 87 MPH, Drive
SUSPENSION, REAR, SINGLE:	13,500-lb Capacity, Vari-Rate Springs
PAINT:	Cab schematic 100CX Location 1: 9219, Winter White (Std) Chassis schematic N/A

(3) 2022 INTERNATIONAL CV515 SFA 4X2 CONVENTIONAL CAB CHASSIS (VIN NH622096 or equal)

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
CV51500	Base Chassis, Model CV515 SFA with 189.00 Wheelbase, 107.80 CA, and 63.00 Axle to Frame.	4671/2886	7557

AXLE CONFIGURATION

1ANA	AXLE CONFIGURATION {Navistar} 4x2	0/0	0
	<u>Notes</u> : Pricing may change if axle configuration is changed.		

ENGINE

12GAG	ENGINE, DIESEL {International 6.6} EPA 2021, 350HP @ 2700 RPM, 700 lb-ft Torque @ 1600 RPM, 2900 RPM Governed Speed, 350 Peak HP (Max)	0/0	0
	<u>Includes</u> : GLOW PLUG Automatic with Indicator Light : OIL FILTER, ENGINE Spin-On Type		
12XCU	CARB EMISSION WARR COMPLIANCE for International 6.6 Engines	0/0	0
12WZB	CARB IDLE COMPLIANCE Low NOx Idle Engine, Complies with California Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood	0/0	0
12VHV	EMISSION, CALENDAR YEAR {International 6.6} EPA, OBD and GHG Certified for Calendar Year 2021	0/0	0
12XZD	RADIATOR Aluminum, 3-Row, Down Flow, Front to Back System, 730 SqIn Louvered, with 578 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler	0/0	0
12TTM	FAN DRIVE Viscous Type, Screw On, Rear Tether, Electronically Controlled	0/0	0
12VGC	AIR CLEANER Single Element, with Water Separator	0/0	0
12WUU	GOVERNOR Electronic Road Speed Type; with 75 MPH Default	0/0	0
12WGG	THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic Controlled, On/Off Switch Mounted on Dash, with Steering Wheel Button Control	0/0	0

TRANSMISSION

13AWY	TRANSMISSION, AUTOMATIC {Allison 1700 RDS} 5th Generation Controls, Close Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Park Pawl, with 19,500-lb GVW and 26,000-lb GCW Max, On/Off Highway	0/0	0
13WVV	NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released	0/0	0
13XAK	PTO LOCATION Customer Intends to Install PTO at Right Side of Transmission	0/0	0
13WYY	SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming	0/0	0

REAR AXLES, SUSPENSIONS

14ACW	AXLE, REAR, SINGLE {Dana Spicer S14-110} Single Reduction, 13,500-lb Capacity, 190 Wheel Ends . Gear Ratio: 4.10	0/0	0
14SAC	SUSPENSION, REAR, SINGLE 13,500-lb Capacity, Vari-Rate Springs	0/60	60
14WMN	AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 1 thru 29.99 Pints	0/0	0
14WAP	SHOCK ABSORBERS, REAR (2)	0/50	50

FRONT AXLES

2AJK	AXLE, FRONT NON-DRIVING {Dana Spicer D-800N} I-Beam Type, 7,000-lb Capacity	0/0	0
------	---	-----	---

Code	Description	F/R Wt (lbs)	Tot Wt (lbs)
FRONT SUSPENSIONS			
3AGN	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 7,000-lb Capacity, with Shock Absorbers	0/0	0
CABS, COWLS, BODIES			
16030	CAB Conventional, Day Cab	0/0	0
	<u>Includes</u> : CAB DOOR LOCKS Power Door Locks All Doors : DOME LIGHT, CAB with OFF/DOOR/ON Settings; Located in Overhead Console : READING LIGHT, CAB Located in Overhead Console : STEP (2) One Per Door : STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door		
16XCP	AIR BAG, FRONT, DRIVER SIDE	0/0	0
16XCR	AIR BAG, FRONT, PASSENGER SIDE	0/0	0
16XDE	AIR BAG, SIDE, DRIVER Seat Mounted, Outboard Side-Impact Airbag	0/0	0
16XDG	AIR BAG, SIDE, PASSENGER Seat Mounted, Outboard Side-Impact Airbag	0/0	0
16XDH	AIR BAG, SIDE CURTAIN Roof Mounted, for Front and Rear Outboard Seating Positions for Driver and Passenger Sides	0/0	0
16XZA	AIR CONDITIONER with Heater, Single Zone	0/0	0
16VKK	CAB INTERIOR TRIM Diamond, for Day Cab	0/0	0
16CEM	COLOR, INTERIOR Dark Ash	0/0	0
16BAN	DOOR HANDLE, EXTERIOR Bright Finish	0/0	0
16HLY	GAUGE CLUSTER English Speedometer, Includes English Odometer; Includes 4.2" Color Display with Personalization, Warning Messages and Vehicle Information	0/0	0
16BBA	GLASS, ALL WINDOWS Solar Absorbing, Tint	0/0	0
16XAL	KEYLESS ENTRY SYSTEM REMOTE with Panic Alarm and Horn Beep Lock Confirmation, Includes Two Key Fob Transmitters	0/0	0
16ACC	MIRROR, INSIDE REAR VIEW with Automatic Dimming	0/0	0
16SPT	MIRRORS (2) Manual Folding and Extending, Power Adjust, Heated, Turn Signal Indicator Located in Mirror, Bright Heads and Arms, for 96" Load Width	5/0	5
16KVU	SEAT, DRIVER High Back with Integral Headrest, 10-Way Power Adjustable, Cloth, Manual Adjust Lumbar	0/0	0
16LVP	SEAT, TWO-MAN PASSENGER High Back with Integral Headrest in Outboard Position, Center Fold-Down Armrest with Storage, Cloth, with Recline	0/0	0
16XCS	SUN VISOR, INTERIOR with Illuminated Mirror for Driver and Passenger Sides	0/0	0
16WAK	WINDOW, POWER (2) in Left and Right Doors	0/0	0
FRAMES			
1CGH	FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield), Straight Top Flange with Contoured Bottom, Height Transitions from 7.375" (187.325mm) to 9.125" (231.775mm) to 7.625" (193.675mm); Width: 3.079" (78.21mm); Thickness: 0.3125" (7.94mm); 383.3" (9735.8mm) Max OAL	61/101	162
1LNZ	BUMPER, FRONT Contoured, Steel, Chrome Plated, for CV and RE Bus	0/0	0
1570	TOW HOOK, FRONT (2) Frame Mounted	13/-1	12
1WND	AF RANGE 50" (128cm) Through and Including 75" (190cm)	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
1WEC	WHEELBASE RANGE 185" (470cm) Through and Including 236" (600cm)	10/30	40
BRAKES			
4240	BRAKE SYSTEM, HYDRAULIC {Bosch} Split System, with Four Channel ABS, Traction Control, Electronic Stability Control, Hydromax Brake Booster with High Speed Master Cylinder and Trailer Sway Control	0/0	0
4GBJ	BRAKE, PARKING {Bosch} DSSA Type, 12" x 3"; for Hydraulic Brake Chassis; Foot Operated in Cab; Differential Mounted	0/0	0
4XCU	BRAKES, FRONT {Meritor Quadraulic} Hydraulic Disc Type, with Four 64mm Diameter Pistons, 8,000-lb Capacity	0/0	0
4EVD	DUST SHIELDS, FRONT BRAKE for Hydraulic Brakes	0/0	0
4XCV	BRAKES, REAR {Meritor Quadraulic} Hydraulic Disc Type, with Four 64mm Diameter Pistons, 15,500-lb Capacity per Axle	0/0	0
4EVE	DUST SHIELDS, REAR BRAKE for Hydraulic Brakes	0/0	0
STEERING			
5PSS	STEERING GEAR {Bosch S2 8014 Plus} Power	0/0	0
5708	STEERING COLUMN Tilting	0/0	0
5CBH	STEERING WHEEL 4-Spoke; 15" Dia., Black, Leather Wrapped	0/0	0
DRIVELINES			
6DGA	DRIVELINE SYSTEM {Dana Spicer} SPL100, for 4x2/6x2	0/0	0
EXHAUST SYSTEMS			
7BLL	EXHAUST SYSTEM Horizontal, Frame Mounted Right Side, Under Rail, for Single Exhaust	0/0	0
7SDS	ENGINE EXHAUST BRAKE for International 6.6 Engine	0/0	0
7XAA	MANUAL REGEN Capability	0/0	0
ELECTRICAL SYSTEMS			
8002	ELECTRICAL SYSTEM 12-Volt for CV Model	0/0	0
	Includes : HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : PARKING LIGHT PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : TURN SIGNALS, FRONT Includes Reflectors and Solid State Flashers; Flush Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature, Integral with Turn Signal Lever		
8GJA	ALTERNATOR {Denso SC2} Brush Type, 12 Volt, 150 Amp Capacity	0/0	0
8VVB	BATTERY BOX Steel, with Plastic Cover, 2 Battery Capacity, Parallel to Rail, 28" Wide, Mounted Left Side Under Cab	0/0	0
8MVZ	BATTERY SYSTEM {VARTA} Maintenance-Free, (2) 12-Volt 1100CCA Total, Top Threaded Stud	0/0	0
8HXV	BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Crew Cab at Left Frame; Includes One Sealed Connector for Separate Ground/Backup/Left and Right Hand Turn, Left and Right Hand Tail/Stop/Accessory Power and Combined for Left and Right Hand Stop/Turn	3/1	4
8XJV	CLEARANCE/MARKER LIGHTS (5) Amber LED Lights, Flush Mounted on Cab	0/0	0

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
8RNS	COMPACT DISC PLAYER with MP3	2/0	2
8XJM	HEADLIGHTS Halogen, Composite Aero Design, Chrome Trim Bezel, with Daytime Running Lights	0/0	0
8VAY	HORN, ELECTRIC Disc Style	0/0	0
8RNP	RADIO AM/FM/Bluetooth/USB Input/Auxiliary Input/SD Card Slot, with 8" Color Touch Panel Display with Navigation, Voice Activated Technology, Satellite Radio Compatible	0/0	0
8RNU	SPEAKERS (6)	2/0	2
8XJW	STARTING MOTOR 12 Volt	0/0	0
8TUL	STOP, TURN, TAIL & B/U LIGHTS Multi-Function, Sealed, Incandescent Stop, Turn and Tail Lights, Backup Lights with Rear Reflex Reflector, Includes License Plate Light	0/0	0
8XJP	SWITCH, AUXILIARY 1 to 4 Latching Switches with 30-Amp Fuses	0/0	0
FRONT END			
9WAY	FRONT END Tilting, Fiberglass, with Three Piece Construction	0/0	0
9WAC	BUG SCREEN Mounted Behind Grille	0/0	0
9WBN	FENDER EXTENSIONS Painted	0/0	0
9HCG	GRILLE Chrome, with Chrome Headlight Bezels	0/0	0
9AAB	LOGOS EXTERIOR Model Badges	0/0	0
SPEEDOMETER, TOOLS, MISC			
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
10XAW	GVWR WEIGHT CLASSIFICATION Class 5 (16,001-19,500 lbs)	0/0	0
10WGE	SPECIAL RATING, GVWR Limited to 19,500-lb GVWR	0/0	0
FUEL TANKS			
15SZN	FUEL TANK Top Draw, Plastic, Rectangular, 17" Tank Depth, 40 US Gal (151L), Includes Auxiliary Draw Port and Fuel Filler Assembly, Mounted Between Frame Rails and Behind Rear Axle	0/0	0
15WDZ	DEF TANK 6.75 US Gal (26L) Capacity, Frame Mounted Outside Right Rail, Under Cab	0/0	0
WHEELS, TIRES - FRONT			
27DTX	WHEELS, FRONT (Accuride 50180) DISC; 19.5x6.75 Rims, Powder Coat Steel, 4-Hand Hole, 8-Stud, 275mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
7779445433	(2) TIRE, FRONT 225/70R19.5 Load Range G HYBRID HS3 (CONTINENTAL), 649 rev/mile, 87 MPH, All-Position	0/0	0
WHEELS, TIRES - REAR			
28DTX	WHEELS, REAR (Accuride 50180) DUAL DISC; 19.5x6.75 Rims, Powder Coat Steel, 4-Hand Hole, 8-Stud, 275mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
7779445428	(4) TIRE, REAR 225/70R19.5 Load Range G HYBRID HD3 (CONTINENTAL), 647 rev/mile, 87 MPH, Drive Cab schematic 100CX	0/16	16

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
	Location 1: 9219, Winter White (Std)		
	Chassis schematic N/A		
	Services Section:		

WARRANTY

40131	WARRANTY Standard for CV515, Effective with Vehicles Built December 3, 2018 or Later, CTS-3000A	0/0	0
	Total Component Weight:	4767/3143	7910
<u>Body/Allied Equipment Code</u>	<u>Description</u>	<u>F/R Wt</u>	<u>Tot Wt</u>
1	Custom 14' flatbed dump body with 40" tall side walls. Installation by Truck Equipment Sales, Mobile AL.	0/0	0
2	Local Post Build	0/0	0
3	Raw Material Surcharge	0/0	0

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.