

G & J's Power Equipment Inc.
211 S. Cypress Street
Foley, AL
36535
(251) 970-1306
(251) 943-1567

Estimate

ASSIGN

1/9/2015

Sold To:

CITY OF FOLEY
P.O. BOX 1750
FOLEY AL 36536

Phone: 424-6375-RICK

Part Number	Description	Ordered	Price	Tax	Total
BC2600HH	26" BRUSH CUTTER BILLY GOAT	1	3,038.75		3,038.75
SH & HDLING	SHIPPING & HANDLING	1	150.00		150.00

Sub Total	\$3,188.75
STATE SALES TAX 4%	\$0.00
COUNTY SALES TAX 3%	\$0.00
CITY SALES TAX 2%	\$0.00
RO STATE 2%	\$0.00
Tax 5 1.25%	\$0.00
RO CITY 0.5%	\$0.00
Total	\$3,188.75

All estimates are subject to a +/- 10% change in value, customer will be notified of any unforeseen problems when estimate was created before any additional repair is performed. Thank you.

HW651HSP

Our high weed mower is a specialty high torque unit designed for cutting knee high grass and weeds. A favorite of municipalities, street crews, school districts, and rental yards, this machine can clean up any overgrown lawn situation with ease. It also doubles as a 24" finish cut mower that is 13 percent more efficient than standard 21" mowers so it can be used all year long.

The unit features:

- 24" width – high torque cut system separates blade from engine crankshaft
- 3 Speed Tuff Torq™ transmission with differential
- 16" rear wheels
- Side discharge
- Operator friendly controls and padded grips
- 4 pt. height adjustment from 2" to 4"
- Premium Honda power
- Powder coat automotive finish for long life paint finish
- Premium bearings
- Rear projectile guard standard



BC2403IC, BC2403H & BC2403HEB

A proven performer since 1995, The Outback® brush hog ideal for clearing brush up to 6' high and saplings up to 2.0" diameter. It's designed to take the abuse of hitting all those items hidden in the brush such as rocks, stumps, fence posts and tires. The heavy duty blade spindle is reinforced in four directions and connects via a heavy duty belt to protect the engine, so you can keep cutting in the harshest environments.

The unit features:

- 24" cut with reinforced spindle
- 3 speed limited slip transaxle with reverse has the benefit of no linkages between the transmission and differential to snag
- Rigid deck design for added stability in brush
- 16" puncture proof tires or optional foam filled tires – Part No. 500352 (Left); Part No. 500353 (Right)
- Protected rear mounted clutch
- Steel hand guard and plow style handles
- No twist belt
- Angled rear discharge deck eliminates packing and wind rows
- Front deck projectile guard, brush bar and solid steel skids



26" Cut

Model	Engine	Start	Cut Width	Height Adj	Productivity	Weight	Length	Width
HW651HSP	6.5 hp Honda	Pull	24"	2-4"	32,735 sq. ft./hr	154lb	62"	32"
BC2403IC	13 hp Briggs	Pull	24"	4"	24,182 sq. ft./hr	257lb	82.5"	27.5"
BC2403H	13 hp Honda	Pull	24"	4"	24,182 sq. ft./hr	269lb	82.5"	27.5"
BC2403HEB	13 hp Honda	Electric	24"	4"	24,182 sq. ft./hr	283lb	82.5"	27.5"