

## **Customer Quote**

_			
_ <		nm	nnt.
_u	uı	pme	511L

Quantity:	1
Truck Price:	\$204,069
Dealer Options:	\$0
Extended Warranty:	\$0
Equipment Price:	\$157,133
Surcharges Not Subject to Discount:	\$0
Options Not Subject to Discount:	\$1,350
Factory Freight Cost:	\$3,225

Total Equipment Price:

\$161,708

NET Sale Price:	\$125,340
Miscellaneous	
FET Tire Credit:	\$0
Net Chassis FET:	\$0
State Tax:	\$0
Body/Trailer/Accessories FET:	\$0
Fees:	\$425
Other:	\$0

**Quotation Total:** 

\$125,765

This quotation worksheet is provided to aid dealers in their pricing efforts. Since PACCAR Inc and its truck divisions have no control over data input and various transactional circumstances that may affect the FET calculation, it is not to be considered tax advice. The dealer should consult his own tax advisor for the proper calculation of any taxes under the variety of circumstances, which may occur.

Price Level: July 1, 2020 Deal: CITY OF FOLEY

Printed On: 8/25/2020 11:13:34 AM

Date: August 25, 2020

Quote Number: QUO-703188-L3Q9Z2





# SOURCEWELL PARTICIPATING DEALER AGREEMENT PETERBILT MOTORS COMPAY CONTRACT #018-716-PMC

This Participating Dealer Agreement dated <u>JUNE 9TH</u>, 2018 is between PETERBILT MOTORS COMPANY, an unincorporated division of PACCAR Inc ("Peterbilt"), located in Denton, Texas and PERFORMANCE PETERBILT ("Dealer"), located in <u>ALBANY</u>, GA.

WHEREAS Peterbilt has entered into an agreement ("Agreement") with Sourcewell as the National Joint Powers Alliance (NJPA) dated November 15,2016 pursuant to which Peterbilt will sell to Sourcewell affiliated government and education agencies through participating Peterbilt dealers certain commercial vehicles subject to the terms and conditions set forth in the Agreement:

WHEREAS Dealer wishes to participate in the sale and service of such commercial vehicles to Sourcewell affiliated government and education agencies ("Sourcewell Members") and agrees to be subject to the terms and conditions set forth in the Agreement:

In consideration of the mutual promises set forth herein, Peterblit and Dealer agree to the following terms and conditions:

- 1. Recitals. The parties agree that the foregoing recitals are true and correct, and are hereby incorporated in and made a part of this agreement.
- 2. Adoption of Obligations of Lessor. Dealer hereby adopts and agrees to be bound by all the terms, conditions, and obligations of the Agreement, the terms and conditions of which are incorporated herein by reference, solely with respect to the vehicles sold to Sourcewell Members by Dealer. Dealer agrees to assume all rights and obligations of Peterbilt as specified in the Agreement solely for vehicles sold by Dealer to Sourcewell Members.
- 3. Term. This Participating Dealer Agreement shall remain effective until terminated by either party upon sixty (60) days' prior written notice.
- 4. Pricing and Order Processing. Dealer agrees that pricing of vehicles to Sourcewell Members shall conform to the not-to-exceed pricing matrix established by Peterbilt, which may be amended from time to time in Peterbilt's sole discretion. Should Dealer charge a sales price in excess of the amount set forth in the pricing matrix, Dealer shall promptly refund the excess of the sales price over the amount set forth in the pricing matrix to the affected Sourcewell Member. Peterbilt shall have sole discretion to determine whether there has been an overcharge. All orders shall include the Sourcewell Sales Code. Dealer shall submit copies of final invoices of all vehicles sold by Dealer to Sourcewell members on a monthly basis.
- 5. Indemnity. Dealer agrees that it will protect, defend, indemnify and hold harmless Peterbilt from any and all losses, claims, sults, costs, damages, expenses and liabilities (including reasonable attorney's fees) arising from Dealer's breach of its obligations under the Agreement or Dealer's negligence, gross negligence, or willful misconduct in connection with this Agreement. Notwithstanding the foregoing, Dealer shall have no obligation or liability under this paragraph 4 with respect to any losses, claims, suits, costs, damages, expenses and liabilities (including reasonable attorney's fees) arising from Peterbilt's negligence, gross negligence, or willful misconduct.

Scanned with CamScanner





# SOURCEWELL PARTICIPATING DEALER AGREEMENT PETERBILT MOTORS COMPAY CONTRACT #018-716-PMC

- 6. Non-Exclusivity. Dealer acknowledges and agrees that Peterbilt will afford, at its sole discretion, other participating dealers, including competitors of Dealer, the opportunity to participate in the sale and service of commercial vehicles to Sourcewell Members.
- 7. No Agency. No agency, partnership, contractor or employment relationship is created by this Agreement. Dealer shall make no representation that Dealer is the agent, partner, employee, or contractor of Peterbilt.
- 8. Assignment. Neither party may assign this Participating Dealer Agreement without the prior written consent of the other.
- 9. Limitation of Liability. Neither party shall be liable to the other for special, indirect, punitive or consequential damages resulting from or arising out of this Participating Dealer Agreement including, without limitation, loss of profit or business interruptions, without regard to the fault or alleged fault of any party.
- 10. Entire Agreement and Amendment. This Participating Dealer Agreement, including the underlying agreement which is incorporated herein by reference, constitutes the entire agreement between the parties concerning the subject matter hereof, and any and all prior agreements and understandings, written and oral, are without effect and superseded by this agreement. The agreement may be amended only by a written instrument signed by both parties.

N WITNESS WHEREOF, the Parties hereto have signed this Participating Dealer Agreement or have caused same to be duly executed by their authorized signatories, on the date(s) noted below.

DEALER NAME]

Performance Petersbilt

Of Albay, LLC

Ignature:

Signature:

Name: ROBERT P. WOODALL

Itle: President

Title: AST. GENERAL MANAGER

Date: 3-11-19

Date: 3-12-19

Scanned with CamScanner



Per.Plt Of Tallahassee (B261) 335 Commerce Blvd. Midway, Florida 32343 CITY OF FOLEY 407 EAST LAUREL AVE. FOLEY, Alabama 36535 United States of America

**Chuck Robinson** 

Cell Phone: 205-420-2711 Office Phone: 850-574-0606

Email: chuck@performancepeterbilt.com

DARRELL RUSSELL

# Vehicle Summary

	Unit	Chassis	
Model:	Model 520	Fr Axle Load (lbs):	20000
Type:	Full Truck	Rr Axle Load (lbs):	44000
Description 1:	CITY OF FOLEY	G.C.W. (lbs):	65400
Description 2:	520 SPEC		
	Application	Road Conditions:	
Intended Serv.:	Refuse/On-Highway	Class A (Highway)	100
Commodity:	Refuse, Scrap, Recycling	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
	Body	Class D (Off-Road)	0
Type:	Automated Side Loader/Push-	Maximum Grade:	6
	Out		
Length (ft):	24	Wheelbase (in):	210
Height (ft):	13.5	Overhang (in):	66
Max Laden Weight (lbs):	1000	Fr Axle to BOC (in):	0.1
· Consider to Freeze		Cab to Axle (in):	209.9
	Trailer	Cab to EOF (in):	275.9
No. of Trailer Axles:	0	Overall Comb. Length (in):	333.6
Type:			
Length (ft):	0	Special Reg.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
1	Restrictions		
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		
Approved by:	-	Date:	

Note: All sales are F.O.B. designated plant of manufacture.

Price Level: July 1, 2020 Deal: CITY OF FOLEY

Printed On: 8/25/2020 11:13:34 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Mo	del			
0005201	S	Model 520 Peterbilt's Model 520 is built to withstand the harsh demands of the refuse industry. The rugged, aluminum cab delivers best-in-class durability for increased uptime and lap seam construction on a zinc-coated steel sub-frame for corrosion resistance. Bulkhead-style doors provide years of watertight performance. This low-cab forward vehicle adds a new dimension of productivity and versatility. An industry-leading, 65-degree cab tilt enhances maintenance and serviceability. Body installation is cost effective and efficient and the center console provides convenient access to body control integration points.	196,670	16,475
0091180	S	Refuse, Scrap, Recycling	0	C
0093035	S	Refuse/On-Highway  Truck or tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills.	0	0
0095220	0	Automated Side Loader/Push-Out  A lift-equipped truck used to pick up wheeled waste containers to load waste materials into the truck body. Requires a single operator. A hydraulic ram pushes the load out of the body.	0	0
0098170	S	United States Registry Canadian Registry PackageRequires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configur	ation			
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame &	Equip	oment		
0514160	0	10-3/4" Steel Rails 306-342" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	176	182
0601500	0	Full Steel Inner Liner	842	672
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	C
0713130	0	(2) Solid Mount Cable Hooks	0	40
Front Ax	le & E	quipment		
1011360	0	Dana Spicer D2000F 20,000 lb, 3.5 in. Drop Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis	504	O

Printed On: 8/25/2020 11:13:34 AM



Code	Std/ Opt	Description	\$ List	Weigh
		EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to		
		protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.		
1114030	S	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	0	(
1243010	S	Power Steering Sheppard M100 Dual For use with 16,000 to 20,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0	,
1354840	0	PHP10 Iron PreSet PLUS Hubs  PHP10 iron PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle.	-686	8-
1380230	0	Dana Spicer 5" Drop IPO 3.5", Front Axle 5" drop (127 MM) provides lower chassis suspension and profile. Offers maximum maneuverability and the light weight solution. Available for a variety of brakes.	0	
1380280	0	Bendix Air Cam Front Drum Brakes 16.5x7 For use with 16,000 lbs to 23,000 lbs steer axles or front drive axles. Includes automatic slack adjusters & outboard mounted brake drums.	755	
1391410	0	Gusseted Cam Brackets, Steer Axle	28	
4000070		Heavy Duty Cam Bushings, Steer Axle	21	
1392970	0	neavy buty cam busings, Steer Axie	31	
		quipment	31	
		Dana Spicer DSH44 44,000 lb, High Performance 44 Interaxle diff lock air rocker occupies space of one gauge. 12.5 mm housing, 15.75 ring gear. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress	-509	
Rear Ax	le & E	Dana Spicer DSH44 44,000 lb, High Performance 44 Interaxle diff lock air rocker occupies space of one gauge. 12.5 mm housing, 15.75 ring gear. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to		-31
<b>Rear Ax</b> 1523330	O	Dana Spicer DSH44 44,000 lb, High Performance 44 Interaxle diff lock air rocker occupies space of one gauge. 12.5 mm housing, 15.75 ring gear. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.  PHP10 Iron PreSet PLUS Hubs  Refuse Service Brakes, Steer And Drive Axles Designed for heavy-duty applications for refuse industry, providing long	-509	-31
<b>Rear Ax</b> 1523330 1616300	O O	Dana Spicer DSH44 44,000 lb, High Performance 44 Interaxle diff lock air rocker occupies space of one gauge. 12.5 mm housing, 15.75 ring gear. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.  PHP10 Iron PreSet PLUS Hubs  Refuse Service Brakes, Steer And Drive Axles Designed for heavy-duty applications for refuse industry, providing long brake life, safety and performance.  Rear Brake Camshaft Reinforcement Rear brake camshaft reinforcement helps guard against wear and	-509	-31
1523330 1616300 1680440	O O	Dana Spicer DSH44 44,000 lb, High Performance 44 Interaxle diff lock air rocker occupies space of one gauge. 12.5 mm housing, 15.75 ring gear. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.  PHP10 Iron PreSet PLUS Hubs  Refuse Service Brakes, Steer And Drive Axles Designed for heavy-duty applications for refuse industry, providing long brake life, safety and performance. Rear Brake Camshaft Reinforcement	-509 -636	-31

Printed On: 8/25/2020 11:13:34 AM



Description	\$ List	Weight
Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure		
exists in the rear air system.		
Upsize Parking Brakes	150	0
Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
Bendix Air Cam Rear Drum Brakes 16.5x8.6  Bendix Air Cam Rear Drum Brakes to fit all heavy haul, contruction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. Refer to TSB 11-57 for more information.	-911	0
Ratio 5.29 Rear Axle	0	0
Hendrickson Haulmaax HMX460 46,000 lb, 54" Axle Hendrickson Haulmaax HMX 460 46,000 lbs, 54" axle spacing, 60,000 lbs. creep rating (during extremely slow operations, typically a crane service)	1,201	-64
pment		
PACCAR PX-9 350@2000 GOV@2200 1150@1400  Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.  N21320 N205 120Standard Maximum Speed Limit N21470 P062 NOCruise Control Auto Resume (N21480 P068 NOAuto Engine Brake in Cruise N21450 P026 NOGear Down Protection (P026) N21440 P015 YESEngine Protection Shutdown (N21350 P001 68Maximum Accelerator Pedal Ve N21370 P059 68Maximum Cruise Speed (P059)	0	0
	Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.  Upsize Parking Brakes  Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.  Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.  Bendix Air Cam Rear Drum Brakes 16.5x8.6 Bendix Air Cam Rear Drum Brakes 16.5x8.6 Bendix Air Cam Rear Drum Brakes 16.5x8.6 Bendix Air Cam Rear Drum Brakes 10 fit all heavy haul, contruction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. Refer to TSB 11-57 for more information.  Ratio 5.29 Rear Axle  Hendrickson Haulmaax HMX 460 46,000 lb, 54" Axle Hendrickson Haulmaax HMX 460 46,000 lb, 54" axle spacing, 60,000 lbs. creep rating (during extremely slow operations, typically a crane service).  pment  PACCAR PX-9 350@2000 GOV@2200 1150@1400 Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevon Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.  N21320 N205 120Standard Maximum Speed Limit N21470 P062 NOCeruise Control Auto Resume (N21480 P068 NOAuto Engine Brake in Cruise N21480 P068 NOCe	Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.  Upsize Parking Brakes  Anti-Lock Braking System (ABS) 4S4M  ABS-6. Includes air braking system.  Synthetic Axle Lubricant All Axles  Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.  Bendix Air Cam Rear Drum Brakes 16.5x8.6  Bendix Air Cam Rear Drum Brakes to fit all heavy haul, contruction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. Refer to TSB 11-57 for more information.  Ratio 5.29 Rear Axle  0  Hendrickson Haulmaax HMX460 46,000 lb, 54" Axle Hendrickson Haulmaax HMX460 46,000 lb, 54" axle spacing, 60,000 lbs. creep rating (during extremely slow operations, typically a crane service).  pment  PACCAR PX-9 350@2000 GOV@2200 1150@1400  Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain pluc captures and holds any metal fragments in engine oil to extend service life.  N21320 N205 120Standard Maximum Speed Limit N21470 P062 NOGruise Control Auto Resume (N21480 P068 NOGear Down Protection (P026) N21440 P015 YESEngine Protection Shutdown (N21480 P016 NOGruise Control Auto Resume (N2148

Printed On: 8/25/2020 11:13:34 AM



Sales Code	Std/ Opt	Description	\$ List	Weigh
		N21610 P172 40Low Ambient Temperature Thre		
		N21630 P171 80High Ambient Temperature Thr		
		N21510 P520 YESEnable Idle Shutdown Park Br		
		N21430 N201 0Reserve Speed Limit Offset (		
		N21410 N202 0Maximum Cycle Distance (N202		
		N21400 N203 252Reserve Speed Function Reset		
		N21420 N206 10Maximum Active Distance (N20		
		N21340 P112 120Hard Maximum Speed Limit (P1		
		N21550 P516 100Engine Load Threshold (P516)		
		N21620 P173 60Intermediate Ambient Tempera		
		N21330 N207 0Expiration Distance (N207)		
		N21500 N209 0Expiration Distance (N209)		
2091310	0	Engine Idle Shutdown Timer Disabled	0	
2091315	0	Enable EIST Ambient Temp Overrule	0	
2004272		Eff FICT NA Evision Miles	0	
2091372		Eff EIST NA Expiration Miles	0	
2091640		Effective VSL Setting NA	0	
2092016	0	Typical Operating Speed 62 MPH	0	
2092032	0	Powertrain Optimized for Performance	0	
		Best analysis for vehicles used in vocational applications or with heavy		
2140200	S	GCWRs.  CARB Engine Idling Compliance	0	
		PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines		
		will include the required factory installed serialized sticker on the drivers		
		door to identify them as meeting the NOx idling standard.		
2147460	S	Bed Plate for PX-9, L9N Engines	0	
		Designed to increase engine longevity by incorporating a stiffener		
		bracket on the bottom side of the engine, inside the oil pan, for		
		additional reinforcement. Required for all PX-9/L9N refuse applications		
		and recommended for other high load 9-liter applications.		
2513060	S	PACCAR 160 Amp Alternator, Brushed	0	
		PACCAR 160 AMP alternator, brushed producing 160 Amps at road		
0=01000		speed and 100 Amps at idle.		
2521090	0	Immersion Type Block Heater 110-120V	80	
		Standard location for 2.1M and 1.9M models is left-hand under cab,		
		Model 520 is in bumper, and for Model 220 it is at the driver step. Plug		
		includes a weather-proof cover that protects the receptacle. This pre-		
		heater keeps the coolant in the engine block from freezing when the engine is not running.		
2522110	0	PACCAR 12V Starter, N/A PACCAR MX Engines	0	
		PACCAR 12-volt electrical system. With centralized power distribution		
		incorporating plug-in style relays. Circuit protection for serviceability, 12-		
		volt light system w/circuit protection circuits number & color coded.		
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA	0	

Printed On: 8/25/2020 11:13:34 AM



Sales Code	Std/ Opt	Description	\$ List We	ight
		Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.		
2539740	0	Kissling Battery Disconnect Switch, 300 amp	160	3
		Mounted on battery box	100	Ū
2621000	S	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0	0
2723210	S	18.7 CFM Air Compressor  N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921110	S	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3010400	0	Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	10	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367	0	0
3120450	S	HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.  Stainless Steel Grille	0	0
3261980	S	Heavy Duty Air Cleaner  Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365300	S	Exhaust Vertical LH DPF/SCR LH Back of Cab Vertical.	0	0
3387870	S	24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	0	0
Transmi	ssion	& Equipment		
4052110	S	Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This	0	0
e Level: Ju	IV 1 20		Date: August 25	20

Printed On: 8/25/2020 11:13:34 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65.		
4210200	0	Reverse ratios: DR-(5.03).  1760 HD Driveline, 1 Midship Bearing	232	-15
4216590	0	1710 Driveline Interaxle	-283	{
4210390	O	For tandem rear axles	-203	-
4252830	0	Allison FuelSense 2.0 Basic Features include: EcoCal shift technology keeps the engine speed at the most efficient level and DynActive Shifting system incorporates a learning algorithm that selects variable shift points to find the ideal balance of fuel economy and performance, based upon the vehicle specifications and environmental parameters. This is valuable for applications with heavy start-stop needs like refuse, city delivery, and construction.	-39	C
4252950	0	Omit Allison Neutral At Stop	0	(
4256020	S	Console Mounted Push Button Shifter Allison Automatic Transmissions or LFNA Electric Vehicle	0	(
4256350	0	Auto Neutral AK, Allison HD/RDS Single steer left-hand or right-hand, add code 4540940 if plumbed to flip valve to actuate service brakes is desired	298	(
4256640	0	Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions.	0	(
4256870	O	Allison Output Function S Neutral Indicator Allison output function S Neutral Indicator for PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in Neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is on. In addition with this configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral.	0	0
Air & Tr	ailer E	quipment		
4510330	S	Bendix AD-IS EP Air Dryer, Heater Bendix Air Treatment Oil Coalescing filter, extended purge. Collects and removes solid, liquid and vapor contaminants before they enter the air brake system.	0	0
4520420	0	Pull Cords All Air Tanks	13	1
4540420	S	Nylon Chassis Hose	0	C
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will	0	(

Printed On: 8/25/2020 11:13:34 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.		
4612000	0	Route AE Lines To Allow Welding Of Sub Frame To top of frame 8" forward of back-of-cab to end-of-frame	527	0
Tires &	Wheels	6		
5064010	S	FF: BR 20ply 315/80R22.5 M870 Efficiency Rating: Fair Diameter= 42.8 inches; SLR= 19.9 inches The Bridgestone M870 is a high scrub All-Position Radial tire designed specifically for urban waste collection.	0	0
5161070	0	RR: BR 14ply 11R22.5 M713 Ecopia  Ecopia is an ultra-fuel-efficient drive radial designed for tandem axle applications in long-haul and regional service.	168	8
5190008	S	Code-rear Tire Qty 08	0	C
5220530	0	FF: Alcoa 89U647 22.5X9.00 Clean Buff Finish Aluminum, Ultra ONE wheels with MagnaForce alloy.	302	-94
5310600	S	RR: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, Two Hand Holes	0	(
5390008	S	Code-rear Rim Qty 08	0	(
Fuel Tai	nks			
5556190	Ο	26" Aluminum 100 Gallon Fuel Tank LH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	154	18
5604100	0	Location LH BOC 100 Gallon	0	(
5650490	S	Fuel Cooler Required with single fuel tank	0	(
5651390	0	Top Of Fuel Tank 5" Below Top Of Frame	583	3
5652890	S	DEF Tank Mounted LH BOC  Models 220 and 520 mounted left hand back-of-cab.	0	
5652990	S	DEF To Fuel Ratio 2:1 Or Greater	0	)
5655069	S	DEF Tank 520	0	
Battery	Box &	Bumper		
6011070	0	Aluminum Battery Box LH Frame Mtd Back-of- Fender Aluminum battery box left hand frame mounted back-of-fender. 8" Below top of frame.	581	

Printed On: 8/25/2020 11:13:34 AM



Sales Code	Std/ Opt	Description	\$ List	Weigh
6122810	0	Steel Bumper Swept Back Painted Requires bumper extension, includes two front tow eyes with pins	-20	2
6132400	0	Notched Top Flange Of Bumper  Does not include fepto provisions	50	(
6132420	0	4-7/8" Bumper Extension, Without FEPTO	226	31
Cab & E	quipm	ent		
6501090	O	Use with auto-trans. Includes steel frames with aluminum and fiberglass panels, all aluminum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, doghouse full insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, adjustable side flip-down interior sunvisor, 16" steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC controls, rear cab corner windows, 18" bolt-on step on each side, self-canceling turn signals and Front Directional and Side Mounted Turn Signals.	1,354	
6800500	S	4.5" Rubber Flares On Cab And wheel well fenders	0	
6911720	S	Peterbilt Driver Seat	0	(
6921720	S	Peterbilt Passenger Seat	0	
6931120	0	Seat Belt Color Orange IPO Standard Black	10	
6939400	0	Air Ride Driver	319	4:
6939440	S	Low Back Driver	0	
6939470	S	Vinyl Driver	0	
6939500	0	Air Ride Passenger	319	4:
6939540	S	Low Back Passenger	0	
6939570	S	Vinyl Passenger	0	)
7000000	S	Gray Interior Color Includes ABS gray headliner & rear cab panel, gray vinyl engine tunnel cover. For LH, RH, and dual steer dual seated power windows are standard on both doors. For dual steer RH stand-up the LH window is power and the RH window is a manual sliding window.	0	
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	

Printed On: 8/25/2020 11:13:34 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
7001620	S	Steering Wheel With Peterbilt Logo	0	0
		Steering Wheel with embossed Peterbilt logo over horn button.		
7110680	S	Exterior Cab Entry Grabhandle Textured; NFPA compliant. Available on Day Cab specifications only.	0	0
7220130	S	Rear Window Back of Cab Standard Tint 18.5in X 54in	0	0
7230350	S	2-Piece Flat Windshield	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7561260	S	Black LH/RH Tri-plane Mirrors, Heated, Motorized, Mounted to Doors. Features: Heated on All Three Surfaces, Upper/Lower Mirrors are Convex and Middle is a Flat Pane Motorized Mirror.	0	0
7610020	S	(1) Air Horn 15" Painted Mounted under cab.	0	0
7722120	0	ConcertClass, AM/FM, Weatherband, 3.5 Aux	422	10
7725740	0	Midlevel Speaker Package For Cab (4) Speakers	135	6
7728040	0	Bluetooth Phone and Audio	62	0
7728050	0	USB Port	62	0
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or	0	0
7788057	0	Cummins Westport natural gas engine.  24 Months SmartLINQ Subscription PACCAR PX Engines.	0	0
7851330	0	Cab Tilt Pump Air Assist	512	0
7851870	0	Rain Gutters Over Driver and Passenger Doors	76	8

Printed On: 8/25/2020 11:13:34 AM



Sales Code	Std/ Opt	Description	\$ List	Weigh
7852150	S	Peterbilt Pantograph Windshield Wipers With intermittent feature.	0	
7900090	0	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	20	1:
7901130	0	Backup Alarm (107 DB)	110	
8011400	S	Main Transmission Oil Temperature Gauge Located in Driver Information Display	0	
8021315	S	Air Restriction Indicator  Mounted on exhaust stanchion	0	
8031120	0	Warning Light Battery Disconnect, Switch Engaged  Marker light external mounted	14	
8071025	0	Manifold Pressure Gauge Located in Driver Information Display	0	
8110090	S	Headlights Single Rectangular Halogen	0	
8120570	S	(5) LED Clearance With (2) LED Marker Lights Includes (5) lights mounted on roof of cab and (1) cab side marker light mounted in front of each cab door	0	
8133900	S	None Furnished Stop/Tail/Backup Lights  Available with full truck only, not available with tractor	0	
8133960	0	Daytime Running Lights  The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	61	
Paint				
8500710	S	Standard Paint Color Selection	-200	
8530770	0	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85700 BUMPER L0001EA BLACK N85500 CAB ROOF L0006EY WHITE N85200 FRAME L0001EA BLACK	0	
Shippin	•			
Options	Not S	subject To Discount		
9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	
9400094	S	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	
9408982	0	Vehicle Layout  Option is not subject to discount. Fleets will be split prior to build so that the charge is applied to only one unit. Quotes will not reflect this.	1,350	

Printed On: 8/25/2020 11:13:34 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
9409800	S	2017 EPA Emissions Engine Warranty Only	0	0
9409869	0	Presentation Created With SmartSpec	0	0

## **Promotions**

### **Order Comments**

Price Level: July 1, 2020 Deal: CITY OF FOLEY

Printed On: 8/25/2020 11:13:34 AM



Total List Price (W/O Freight & Warranty & Surcharges ) \$204,069

Marketing and Service Support Fee \$875

Prepaid Freight \$3,225

Total Surcharge/Options Not Subject To Discount \$1,350

Total Weight 17,200

## Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

#### PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information

Price Level: July 1, 2020 Deal: CITY OF FOLEY

Printed On: 8/25/2020 11:13:34 AM



### Deena Townsend <a href="mailto:cityoffoley.org">dtownsend@cityoffoley.org</a>

# FW: FW: Sourcewell Quote - New Way Sidewinder XTR 33 cu yd

1 message

Darrell Russell <a href="mailto:cityoffoley.org">drussell@cityoffoley.org</a> To: Deena Townsend <a href="mailto:cityoffoley.org">dtownsend@cityoffoley.org</a> Tue, Sep 22, 2020 at 11:58 AM

### **Darrell Russell**

**Public Works Superintendent** 

(251) 943-8897 office

From: Eden Lapham [mailto:elapham@cityoffoley.org]

Sent: Tuesday, September 22, 2020 11:58 AM

To: DARRELL RUSSELL

Subject: Fwd: FW: Sourcewell Quote - New Way Sidewinder XTR 33 cu yd

----- Forwarded message ------

From: Darrell Russell <a href="mailto:drussell@cityoffoley.org">drussell@cityoffoley.org</a>

Date: Thu, Jun 11, 2020 at 5:34 AM

Subject: FW: Sourcewell Quote - New Way Sidewinder XTR 33 cu yd

To: Jeffrey Cotton <jcotton@cityoffoley.org>, Chris Dyes <cdyes@cityoffoley.org>, Eden Lapham

<elapham@cityoffoley.org>

#### **Darrell Russell**

**Public Works Superintendent** 

(251) 943-8897 office

From: Jeff Bodiford [mailto:jeffb@secequip.com]

Sent: Wednesday, June 10, 2020 4:43 PM

To: Darrell Russell Cc: Jeff Bodiford

Subject: Sourcewell Quote - New Way Sidewinder XTR 33 cu yd

Darrell,

Find attached your requested quote for the New Way ASL. Thank you for your interest in our products and please let me know if you have any questions.

Regards,

Jeff Bodiford

Eden Lapham

City of Foley Public Works

Administrative Assistant IV

120 E Orchid Ave, Foley, AL 36535

(251) 943-8897 / fax: (251) 970-2086

elapham@cityoffoley.org



#### 2 attachments



image002.jpg





#### Deena Townsend <a href="mailto:cityoffoley.org">dtownsend@cityoffoley.org</a>

### **FW: 520 PRESENTATION**

1 message

Darrell Russell <a href="mailto:cityoffoley.org">drussell@cityoffoley.org</a> To: Deena Townsend <a href="mailto:cityoffoley.org">dtownsend@cityoffoley.org</a> Tue, Sep 22, 2020 at 11:53 AM

### **Darrell Russell**

Public Works Superintendent

(251) 943-8897 office

From: Chuck Robinson Jr [mailto:chuck@ppblt.com]

Sent: Tuesday, August 25, 2020 5:58 PM

To: drussell@cityoffoley.org

Cc: Cj White

Subject: 520 PRESENTATION

Darrell,

It was a pleasure meeting with you last week. I look forward to working with you and your people.

I have attached the presentation package for the 520 garbage chassis along with a quote for you. Please let me or C J know if we can be of any assistance.

Thanks!

Chuck



**Chuck Robinson** 

Vice President of Truck Sales

Performance Peterbilt of Tallahassee LLC.

Performance Peterbilt of Albany, GA

Performance Peterbilt of South Georgia, LLC

Performance Peterbilt of West Florida LLC.

cell# 205-420-2711

office# 850-574-0606

fax# 850-574-2790

www.performancepeterbilt.com

" 2013 Platinum Parts & Service Dealer of the year"

"2014 & 2015 Best in Class Dealer of the year"

