

TEXAS LOCAL GOVERNMENT PURCHASING COOPERATIVE BUYBOARD

Vendor	RUSH TRUCK CENTER	Date Prepared	2/3/2015
Contact for Vendor:	DREW NEUBAUER	Phone	830-626-5254
End User:	City of Foley		
End User Contact:		Phone/Fax	251-943-1545
Product Description:	Peterbilt 348		

A: Base Price in Bid/Proposal Number: 430-13			Series: 348 \$71,360.00		
B: Published Options (Itemize Below)					
	DESCRIPTION	AMOUNT		DESCRIPTION	AMOUNT
Peterbilt	Dana Spicer DSP41 40,000 lb.	\$ 8,039.00	RTC-0004	14' Dump Body	\$ 18,113.00
Peterbilt	Hendrickson Haulmax HMX400	\$ 3,558.00	RTC0051	PDI	\$ 1,236.00
Peterbilt	10 5/8 rails with full liner	\$ 1,233.00	RTC0053	Body Prep	\$ 2,438.00
Peterbilt	Fuller RTO 8LL 10 speed	\$ 1,922.00			
Peterbilt	PX9 330 HP/1000 TQ	\$ 2,867.00			
Subtotal Column 1:		\$ 17,619.00	Subtotal Column 2:		\$ 21,787.00
Published Options added to Base Price (Subtotal of "Col 1" & "Col 2")					\$ 39,406.00

C: Subtotal of A + B					\$110,766.00
D: Non Published Options					
	Warren Frame Type, 36" sides	-\$5,166.00			
Subtotal Column 1:		-\$5,166.00	Subtotal Column 2:		\$ -

Unpublished Options added to Base price (Subtotal "Col 1 + Col 2")	-\$5,166.00
--	-------------

E: Contract Price Adjustment (If any, explain here)			

F: Total of C + D +/- E	\$ 105,600.00
-------------------------	---------------

G: Quantity ordered Units: <u>1.00</u> x F	\$ 105,600.00
--	---------------

H: BUYBOARD Administrative Fee	%	\$ 400.00
--------------------------------	---	-----------

I: Non-Equipment Charges & Credits (I.e.: Ext. Warranty, Trade-In, Delivery, etc.)					

J: TOTAL PURCHASE PRICE INCLUDING (G+H+I)	\$106,000.00
---	--------------



Rush Truck Center - Mobile M270
5500 Linwood Steiner Rd

City of Foley
407 East Laurel

Theodore, Alabama United States 36582
Phone: (800) 239-4608
Fax: (251) 459-7301
Email:

Foley, Alabama United States 36535
Phone: (251) 943-1545
Fax:
Contact Email:
Prepared for:

Vehicle Summary

Unit		Chassis	
Model:	Model 348	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs)	40000
Description:	Warren Dump Body	G.C.W. (lbs):	52000
Application		Road Conditions:	
Intended Serv.:	Construction Dump-On/Off Highway	Class A (Highway)	100
Commodity:	Construction Materials	Class B (Hwy/Mtn)	0
Body		Class C (Off-Hwy)	0
Type:	End Dump	Class D (Off-Road)	0
Length (ft):	14	Maximum Grade:	6
Height (ft):	13.5	Wheelbase (in):	178
Max Laden Weight (lbs):	11200	Overhang (in):	62.7
Trailer		Fr Axle to BOC (in):	69.8
No. of Trailer Axles:	0	Cab to Axle (in):	108.2
Type:		Cab to EOF (in):	170.9
Length (ft):	0	Overall Comb. Length (in):	311
Height (ft):	0.0	Special Req.	
Kingpin Inset (in):	0	United States Registry	
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/3/2015 2:29:25 PM
Effective Date: Jan 1, 2015
Prepared by: Administrator

Complete

Model Number: Model 348
Quote/DTPO/CO: Q81027082
Version Number: 30.00



Rush Truck Center - Mobile M270
5500 Linwood Steiner Rd

City of Foley
407 East Laurel

Theodore, Alabama United States 36582
Phone: (800) 239-4608
Fax: (251) 459-7301
Email:

Foley, Alabama United States 36535
Phone: (251) 943-1545
Fax:
Contact Email:
Prepared for:

Description

Base Model

Model 348

Construction Materials

Construction Dump-On/Off Highway

Truck or tractor without liftable trailing axle which carries bulk materials (excavated earth, sand/gravel, asphalt, demolition debris, etc.) and unloads by dumping out the back, over the side of the body, or out the bottom of the trailer.

End Dump

United States Registry

Configuration

Not Applicable
Secondary Manufacturer

Frame & Equipment

10-5/8in Steel Rails to 285in

10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair

Full Steel Inner Liner

178in Wheelbase

Three-Piece Crossmembers

EOF Square without Xmbr

For use with body builder installed crossmember.

Omit Rear Mudflaps and Hangers

Front Axle & Equipment

Dana Spicer E1202I 12,000 lb

3.5" drop. Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD® FE75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.

Taper Leaf Springs, Shocks 12,000 lb

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/3/2015 2:29:25 PM
Effective Date: Jan 1, 2015
Prepared by: Administrator

Complete

Model Number: Model 348
Quote/DTPO/CO: Q81027082
Version Number: 30.00



Description

Power Steering Sheppard HD94

Power Steering Reservoir Frame Mounted

PHP10 Aluminum LMS Hubs

11-1/4" bolt circle. Includes a supplier extended coverage up to 3 years / 350,000 miles for bearings & seals.

Dana Spicer Wide Track IPO Std, Front Axle

71in KPI IPO 69in for E1202, E1322, E1462, D2000F front axles. For improved turning radius.

Bendix Air Cam Front Drum Brakes 16.5x5

For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.

Gusseted Cam Brackets, Steer Axle

Rear Axle & Equipment

Dana Spicer DSP41 40,000 lb

Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.

PHP10 Iron LMS Hubs

11-1/4" bolt circle. Includes a supplier extended coverage up to 3 years / 350,000 miles for bearings & seals.

Parking Brakes (Axle Package)

Gusseted Cam Brackets, Drive Axle(s)

SBM Valve

Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.

Stability System Not Selected or Not Available

Anti-Lock Braking System (ABS) 4S4M

ABS-6. Includes air braking system.

Synthetic Axle Lubricant All Axles

Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/3/2015 2:29:25 PM
Effective Date: Jan 1, 2015
Prepared by: Administrator

Complete

Model Number: Model 348
Quote/DTPO/CO: Q81027082
Version Number: 30.00



Description

Bendix Air Cam Rear Drum Brakes 16.5x7
Inc automatic slack adjusters & outboard mounted brake drums.

Tandem Drive Axle (Model 348)

Ratio 4.63 Rear Axle

Hendrickson Haulmaax HMX400 40,000 lb, 54in Axle
Spacing, 55K Creep Rating

Shock Absorbers For HMX Suspension

Engine & Equipment

PACCAR PX-9 330@2000 GOV@2200 1000@1400

(2013 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 15W40 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.

N21320 N205 120..Standard Maximum Speed Limit [LSL]

N21330 N207 0....Expiration Distance

N21340 P005 120..Hard Maximum Speed Limit

N21350 P001 75...Maximum Accelerator Pedal Vehicle Speed

N21360 P110 0....Accelerator Lower Droop

N21370 P059 75...Maximum Cruise Speed

N21380 P111 0....Cruise Control Lower Droop

N21400 N203 252..Reserve Speed Function Reset Distance

N21410 N202 0....Maximum Cycle Distance

N21420 N206 10...Maximum Active Distance

N21430 N201 0....Reserve Speed Limit Offset

N21440 P015 No...Engine Protection Shutdown

N21450 P026 No...Gear Down Protection

N21460 P046 1400.Max PTO Speed

N21470 P062 No...Cruise Control Auto Resume

N21480 P068 No...Auto Engine Brake in Cruise

N21500 N209 0....Expiration Distance

N21510 P520 Yes..Enable Idle Shutdown Park Brake Set

N21520 P030 5....Timer Setting

N21530 P233 Yes..Enable Impending Shutdown Warning

N21540 P234 60...Timer For Impending Shutdown Warning

N21550 P516 35...Engine Load Threshold

N21570 P031 No...Idle Shutdown Manual Override

N21590 P230 Yes..Enable Hot Ambient Automatic Override

N21610 P172 40...Low Ambient Temperature Threshold

N21620 P173 60...Intermediate Ambient Temperature Threshold

N21630 P171 80...High Ambient Temperature Threshold

Engine Idle Shutdown Timer Enabled

Enable EIST Ambient Temp Override

Eff EIST NA Expiration Miles

Effective VSL Setting NA

CARB Engine Idling Compliance DECLINED By
Dealer/Customer

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/3/2015 2:29:25 PM
Effective Date: Jan 1, 2015
Prepared by: Administrator

Complete

Model Number: Model 348
Quote/DTPO/CO: Q81027082
Version Number: 30.00



Description

PACCAR 160 Amp Alternator, Brushed

PACCAR 12V Starter

2 PACCAR Premium 12V Dual Purpose Batt 1400 CCA

Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.

Battery Jumper Terminal Mounted Under Hood

LH Frame Rail. Not available with PX-7 engines.

Batteries In LH Box U/Cab

2-Speed Fan Clutch For Frequent Start/Stops

18.7 CFM Air Compressor

Furnished on engine. Teflon lined stainless steel braided compressor discharge line.

Spin-on Fuel Filter Frame Mounted, Unheated

In addition to the fuel filter supplied with the engine.

Engine Protection Shutdown

Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.

High Efficiency Cooling System

Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage.

Radial Seal, Dry Type Air Cleaner, Frontal

Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.

Exhaust Single RH Side Of Cab

DPF/SCR RH under cab. Includes cab entry RH under cab and full round stainless steel exhaust guard.

Curved Tip Standpipe(s)

18in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)

Transmission & Equipment

Fuller RTO11908LL 10 Speed

1150 Torque - rear transmission support, direct shift pattern. Synthetic lubricant to reduce friction, improve efficiency, & extend component life. Magnetic transmission oil drain plug captures & holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake.

1760 HD Driveline, Single Midship Bearing

(1) Dash Mounted Single Acting Air PTO Control

Standard with PTO engaged indicator light on Class 8 units. Occupies the space of one gauge.

Allison FuelSense Not Desired

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/3/2015 2:29:25 PM
Effective Date: Jan 1, 2015
Prepared by: Administrator

Complete

Model Number: Model 348
Quote/DTPO/CO: Q81027082
Version Number: 30.00



Description

Manual Shifter, Black

Solo Clutch IPO Easy Pedal

Includes Self-Adjusting Clutch w/Grease Bearing. Refer to Option Portfolio\Drivetrain\Transmission-Clutch section for description of clutch based on your application.

Air & Trailer Equipment

Bendix AD-IS Air Dryer with Heater

An integrated system air dryer that incorporates the functions of the air dryer, purge reservoir (which increases the drying capacity), wet air tank, pressure relief valve, single check valves, and pressure protection valve for air susp and other air accessories. Includes easy-to-service spin-on dessicant cartridge.

Berg Pull Cord Drain Valve(s) - All Air Tanks

Nylon Chassis Hose

Steel Painted Air Tanks

All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.

Body Connections 5ft BOC

Junction Box contains light and power circuits for Body Connections located 5ft from BOC.

Trailer Hand Valve

A&E Conn EOF w/7-way Socket (w/Conn EOF Strapped to the rail)

Tires & Wheels

FF: GY 14ply 11R22.5 G661 HSA

RR: GY 14ply 11R22.5 G572A LHD

Fuel Max

Code-rear Tire Qty 08

FF: Accur Stl Armor 50344PK 22.5X8.25

Heavy duty, 5 Hand Holes

RR: Accur Steel Armor 50344PK 22.5X8.25

Heavy Duty, 5 Hand Holes

Code-rear Rim Qty 08

Fuel Tanks

23in Aluminum 50 Gallon fuel Tank LH BOC

Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/3/2015 2:29:25 PM
Effective Date: Jan 1, 2015
Prepared by: Administrator

Complete

Model Number: Model 348
Quote/DTPO/CO: Q81027082
Version Number: 30.00



Description

Location LH BOC 50 Gallon

DEF Tank Mounted LH BOC

Models 210, 220 and 320 mounted LH cab fender.

DEF Tank Small

Battery Box & Bumper

Steel Battery Box LH Under Cab, Non-Slip Step

Rubber Battery Pad In Bottom Of (1) Battery Box

(Mat in box that holds batteries only)

Aftertreatment Aluminum DPF Cab Entry RH UnderCab

Non-slip step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box will be aerodynamic.

Steel Styled Aero Bumper Painted Cab Color

Two Tow Pins

Cab & Equipment

Alum Cab 108in BBC Metton Hood w/Bright Crown

Includes view window RH door and convex mirror over RH door.

Severe Service Cab Package #1

Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.

Peterbilt UltraRide Driver Seat

Peterbilt UltraRide Passenger Seat

Drivers Armrest - RH Only

Required in Model 587 with Evolution LX seats. Optional with Evolution ST and Rolltek Seats.

Black Seat Color ipo Standard Color

Air Ride Driver

High Back Driver

Mordura Driver

Non-Air Ride Passenger

High Back Passenger

Mordura Passenger

Adjustable Steering Column - Tilt/Telescope

Steering Wheel with Peterbilt Logo

Steering Wheel with embossed Peterbilt logo over horn button.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/3/2015 2:29:25 PM
Effective Date: Jan 1, 2015
Prepared by: Administrator

Complete

Model Number: Model 348
Quote/DTPO/CO: Q81027082
Version Number: 30.00



Description

Interior Grey/Black

Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.

Extended Rear Window ipo Std Window-Day Cab

The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace.

Day Cab Rear Window

One Piece Curved Windshield

Combo Fresh Air Heater/Air Conditioner

With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.

Stainless Steel Mirrors 7x16 with Heat Element

(2) Convex 8 Inch SS Mirror

Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.

Brackets 109in Wide Rear View Mirror

These mirrors to measure 114in center to center.

(1) Air Horn 15in Painted

Mounted under cab.

Standard Speaker Package For Cab

(2) Speakers

ConcertClass Without CD, Includes BT Phone and

Audio, AM/FM, WB, USB and MP3.

CB Terminals/Wiring Mtd Under Header

Radio Antenna Mounted on RH Mirror Bracket

Plug-In Auto Reset Circuit Breaker

in place of fuses in junction box.

Peterbilt Electric Windshield Wipers

With Intermittent Feature.

Triangle Reflector Kit Shipped Loose

5 lb 3A:40bc Fire Extinguisher Cab Mounted

Air Restriction Indicator

Mounted on air cleaner or intake piping.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/3/2015 2:29:25 PM
Effective Date: Jan 1, 2015
Prepared by: Administrator

Complete

Model Number: Model 348
Quote/DTPO/CO: Q81027082
Version Number: 30.00



Description

Main Instrumentation Panel w/Graphics Display

Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.

Headlights Composite Fender Mounted

Integral Park, Turn, and Side Marker

(5) Marker Lights, Aero LED

Light Emitting Diodes

Paint

Axalta Single Stage Non-Metallic Cab/Hood

(Solid Color Paint)

N85020	A -	N0006EA	WHITE
N85400	HOOD TOP	N0006EA	WHITE
N85500	CAB ROOF	N0006EA	WHITE
N85200	FRAME	N0001EA	BLACK
N85700	BUMPER	N0006EA	WHITE
N85300	FENDER	N0006EA	WHITE

Shipping Destination

Shipping Destination

(Specify by narrative)

Options Not Subject To Discount

Medium Duty Emissions Surcharge

Miscellaneous

Total Weight

14786

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/3/2015 2:29:25 PM

Complete

Model Number:

Model 348

Effective Date: Jan 1, 2015

Quote/DTPO/CO:

Q81027082

Prepared by: Administrator

Version Number:

30.00



Quote WIQ-014453

Page 1 of 2
Date 2/2/2015

Warren, Inc.
707 North Fir
COLLINS MS 39428

Phone (800) 228-4842
Fax (601) 765-4554
DumpTrucks.com

Bill To	Ship To	Contact
RUSH TRUCK CENTER 5500 LINWOOD STEINER ROAD THEODORE AL 36582	RUSH TRUCK CENTER 5500 LINWOOD STEINER ROAD THEODORE AL 36582	C J WHITE - CITY OF FOLEY (251) 459-7300 Ext. 0000

Purchase Order No.		Customer ID	Salesperson ID	Shipping Method	Payment Terms	Req Ship Date	Master No.
CITY OF FOLEY		RUS582	CINDY SULLIVAN	CUSTOMER PICKUP	TO BE ARRANGED	0/0/0000	33,405
QTY	Item Number	Description			UOM	Unit Price	Ext. Price
1	F-14	DUMP BODY - FRAME TYPE - 14' Yardage: 10/12 Floor Material: 1/4 A1011 Front / Material: 48" 10 GA A1011 Side / Material: 36" 10 GA A1011 Vertical Side Brace: Yes Horizontal Brace: No Hoist / Cylinder: VTW-63110 Hydraulics: Yes			EA	\$12,400.00	\$12,400.00
1	TAILGATE	Air Operated: Yes Panel: 6 Material: 10 GA A1011 Height: 44" Slope: None Chains: 5/16" Double Acting: Yes High Lift Gate: No Side Swing - Ground Operated: No Center Opening: No Material Gate: None Water Tight: None			Each	\$0.00	\$0.00
1	DB OPTIONS # 1	Cabshield: Full Width 1/2 Asphalt Apron: 8" Bolt On: No Center Board Pockets Yes Lights: LED Standard Oval S/T/T: None Clear Backup: No			Each	\$0.00	\$0.00
1	INSTALL	Hydraulic Hoses/Fittings: Yes Pump: 35 gal w/air shift CCW Console: Air/Air Conspicuity Tape: No Mudflaps and Brackets: Yes Chrome Turnouts: No Splash/Gravel Guards: No Side Boards: Steel- 2x8 Covers: No Wires in Conduit No Delivery Fuel/Charges: No			Each	\$0.00	\$0.00
1.00	PAINT	ANY STANDARD WARREN PAINT Std gloss black urethane enamel			GAL	\$0.00	\$0.00
1	PTO	AIR SHIFT FOR MANUAL TRANSMISSION			EA	\$0.00	\$0.00
1	TARP SYSTEM	TARP svstem - installed			EA	\$0.00	\$0.00



Quote WIQ-014453

Page 2 of 2
Date 2/2/2015

Warren, Inc.
707 North Fir
COLLINS MS 39428

Phone (800) 228-4842
Fax (601) 765-4554
DumpTrucks.com

Purchase Order No.		Customer ID	Salesperson ID	Shipping Method	Payment Terms	Req Ship Date	Master No.	
CITY OF FOLEY		RUS582	CINDY SULLIVAN	CUSTOMER PICKUP	TO BE ARRANGED	0/0/0000	33,405	
QTY	Item Number	Description				UOM	Unit Price	Ext. Price
1	TOW PACKAGE	Installation: Installed Brand: Donovan Manual / Electric: Electric Type: Arm Aluminum / Steel: Aluminum Bent Arm: No Tarp Size: 90"x18' Tarp Type: Asphalt Side Flaps: No				Each	\$0.00	\$0.00
		Pintle Plate: 3/4" Pintle Hitch: 25Ton (spring mt) Glad Hands: as required D Rings: Yes Tow Hooks: No Electric Plug: 7 Way Pup Rigging: No						

QUOTATION VALID FOR 30 DAYS

Subtotal	\$12,400.00
Misc	\$0.00
Tax	\$0.00
Ship & Handling	\$0.00
Trade In Allowance	\$0.00
Total	\$12,400.00