



Mobile AL
5500 Linwood Steiner Rd
Theodore, AL 36582
251-459-7300
800-239-4608

Customer Proposal Letter

City of Foley
407 East Laurel Ave.
Foley, AL 36535
(251) 943-1545

Thank you for the opportunity to earn your business. We look forward to working with you on your business needs. Please accept the following proposal.

VEHICLE

Make Peterbilt Model 520 Year 2020 ✓ Stock Number To Be Determined
Additional Vehicle and Accessories Description _____ To be delivered on or about _____

Quantity	1	Total
Truck Price per Unit	\$129,500.00	\$129,500.00
F.E.T. (Factory & Dealer Paid)	\$0.00	\$0.00
Net Sales Price	\$129,500.00	\$129,500.00
Optional Extended Warranty(ies)		
State Sales Tax		
Documentary Fee	\$250.00	\$250.00
Electronic Filing	\$15.00	\$15.00
Administration Fee		
Vehicle Inventory Tax		
Additional Taxes		
Tire Recycling Program		
Battery Disposal Fee		
Out of State Vehicle Fee		
Rebate(s)		
Total Sales Price (Including Rebate(s))	\$129,765.00	\$129,765.00 ✓
Trade Allowance (see DISCLAIMER Below)		\$0.00

Sales Representative

Purchaser

Accepted by Sales Manager or
General Manager

signature

signature

title

signature

Todd Tracy

printed name

printed name

date

printed name

Quote good until 3/14/2019

Note: The above Customer Proposal is a quotation only. Sale terms subject to approval of Sales Manager of Dealer.

DISCLAIMER: Any order based on this Proposal subject to Customer executing Dealer's standard form Retail Purchase Order incorporating above terms. Any documentary fees, state tax, title, registration and license fees subject to adjustment and change. Actual F.E.T. to be paid by Dealer, subject to adjustment. Any F.E.T. variance will be responsibility of Dealer. Manufacturer has reserved the right to change the price to Dealer of any vehicle not currently in Dealer's stock, without notice to Dealer. If Quoted Vehicle(s) not currently in Dealer's stock, Dealer reserves right to change Quotation Total to reflect any price increases from Manufacturer. This Proposal is based upon Dealer's current and expected inventory, which is subject to change. Dealer not obligated to retain any specific vehicles in stock, nor maintain any specific inventory level. Dealer shall not be obligated to fulfill Proposal in event quoted vehicle(s) not in stock or available within requested delivery schedule at time Proposal accepted. Dealer shall not be liable for any delay in providing or inability to provide Quoted Vehicle(s), where such inability or delay is due, in whole or in part, to any cause beyond the reasonable control of Dealer or is without the gross negligence or intended misconduct of Dealer. Above listed Trade Value based upon current appraisal of Trade Vehicle(s). Dealer may adjust Trade Value of Trade Vehicle(s) to reflect changes in condition and/or mileage of Trade Vehicle(s) between date of current appraisal and acceptance of this Proposal by Customer.



Rush Truck Center, Mobile M270
5500 Linwood Steiner Rd

City of Foley
407 East Laurel

Theodore, Alabama United States 36582
Phone: (251) 459-7300
Fax: (251) 459-7301
Email:

Foley, Alabama United States 36535
Phone: (251) 973-1545
Fax: (251) 952-4014
Contact Email:
Prepared for: Darrell Russell

Vehicle Summary

Unit		Chassis	
Model:	Model 520	Fr Axle Load (lbs):	18740
Type:	Full Truck	Rr Axle Load (lbs)	44000
Description:	520 RH	G.C.W. (lbs):	62000
Application		Road Conditions:	
Intended Serv.:	Refuse/On-Highway	Class A (Highway)	100
Commodity:	Refuse, Scrap, Recycling	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:	Automated Side Loader/Push-Out	Wheelbase (in):	210
Length (ft):	24	Overhang (in):	66.10001
Height (ft):	13.5	Fr Axle to BOC (in):	0.1
Max Laden Weight (lbs):	1000	Cab to Axle (in):	209.9
		Cab to EOF (in):	276.0
Trailer		Overall Comb. Length (in):	333
No. of Trailer Axles:	0		
Type:		Special Req.	
Length (ft):	0	United States Registry	
Height (ft):	0.0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/12/2019 9:38:28 AM
Effective Date: Jan 1, 2019
Prepared by: Administrator

Complete

Model Number: Model 520
Quote/DTPO/CO: Q64227141
Version Number: 38.10



Rush Truck Center, Mobile M270
5500 Linwood Steiner Rd

City of Foley
407 East Laurel

Theodore, Alabama United States 36582
Phone: (251) 459-7300
Fax: (251) 459-7301
Email:

Foley, Alabama United States 36535
Phone: (251) 973-1545
Fax: (251) 952-4014
Contact Email:
Prepared for: Darrell Russell

Data	Code	Description	\$ List	Weight
Base Model				
0005201	O	Model 520 Peterbilt's Model 520 is built to withstand the harsh demands of the refuse industry. The rugged, aluminum cab delivers best-in-class durability for increased uptime and lap seam construction on a zinc-coated steel sub-frame for corrosion resistance. Bulkhead-style doors provide years of watertight performance. This low-cab forward vehicle adds a new dimension of productivity and versatility. An industry-leading, 65-degree cab tilt enhances maintenance and serviceability. Body installation is cost effective and efficient and the center console provides convenient access to body control integration points.	193,763	16,475
0091180	O	Refuse, Scrap, Recycling	0	0
0093035	O	Refuse/On-Highway Truck or tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills.	0	0
0095220	O	Automated Side Loader/Push-Out	0	0
0098170	O	United States Registry	0	0
Configuration				
0200700	O	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514160	O	10-3/4in Steel Rails 306-342in 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	149	180
0601500	O	Full Steel Inner Liner	683	672
0644090	S	EOF Square without Xmbr For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
0713130	O	(2) Solid Mount Cable Hooks	0	40

Front Axle & Equipment

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/12/2019 9:38:28 AM
Effective Date: Jan 1, 2019
Prepared by: Administrator

Complete

Model Number: Model 520
Quote/DTPO/CO: Q64227141
Version Number: 38.10



Data	Code	Description	\$ List	Weight
1011360	O	Dana Spicer D2000F 20,000 lb, 3.5 in. Drop Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	483	0
1114030	S	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	0	0
1243020	O	Power Steering Sheppard SD110 Dual For use with 22,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0	0
1354840	O	PHP10 Iron PreSet PLUS Hubs	-858	84
1380230	O	Dana Spicer 5in Drop IPO 3.5in, Front Axle 5" drop (127MM) provides lower chassis suspension and profile.	0	0
1380270	O	Bendix Air Cam Front Drum Brakes 16.5x6 Includes automatic slack adjusters & outboard mounted brake drums.	464	0
1391410	O	Gusseted Cam Brackets, Steer Axle	28	0

Rear Axle & Equipment

1523330	O	Dana Spicer DSH44 44,000 lb, High Performance 44 Interaxle diff lock air rocker occupies space of one gauge. 12.5 mm housing, 15.75 ring gear. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	-507	-311
1616300	O	PHP10 Iron PreSet PLUS Hubs	-820	0
1632650	S	Long Stroke Parking Brakes, Drive Axle(s)	0	0
1680440	O	Refuse Service Brakes, Steer And Drive Axles	0	0
1680450	O	Rear Brake Camshaft Reinforcement	62	9
1680490	O	Gusseted Cam Brackets, Drive Axle(s)	71	2
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680550	O	Upsize Parking Brakes	153	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/12/2019 9:38:28 AM
Effective Date: Jan 1, 2019
Prepared by: Administrator

Complete

Model Number: Model 520
Quote/DTPO/CO: Q64227141
Version Number: 38.10



Data	Code	Description	\$ List	Weight
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687020	O	Bendix Air Cam Rear Drum Brakes 16.5x8.6 Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. Refer to TSB 11-57 for more information.	-1,080	0
1705290	O	Ratio 5.29 Rear Axle	0	0
1824240	O	Hendrickson Haulmaax HMX460 46,000 lb, 54in Axle Spacing, 60K Creep Rating	1,046	-64

Engine & Equipment

2074406	S	PACCAR PX-9 350@2000 GOV@2200 1150@1400 Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 75...Standard Maximum Speed Limit [LSL] N21330 N207 0....Expiration Distance N21350 P001 72...Maximum Accelerator Pedal Vehicle Speed N21370 P059 72...Maximum Cruise Speed N21400 N203 252...Reserve Speed Function Reset Distance N21410 N202 0....Maximum Cycle Distance N21420 N206 10...Maximum Active Distance N21430 N201 0....Reserve Speed Limit Offset N21440 P015 YES...Engine Protection Shutdown N21450 P026 NO...Gear Down Protection N21460 P046 1400.Max PTO Speed N21470 P062 NO...Cruise Control Auto Resume N21480 P068 NO...Auto Engine Brake in Cruise N21500 N209 0....Expiration Distance N21510 P520 YES...Enable Idle Shutdown Park Brake Set N21520 P030 5....Timer Setting N21530 P233 YES...Enable Impending Shutdown Warning N21540 P234 60...Timer For Impending Shutdown Warning N21550 P516 35...Engine Load Threshold N21570 P031 NO...Idle Shutdown Manual Override N21590 P230 YES...Enable Hot Ambient Automatic Override N21610 P172 40...Low Ambient Temperature Threshold N21620 P173 60...Intermediate Ambient Temperature Threshold N21630 P171 80...High Ambient Temperature Threshold	0	0
2091305	O	Engine Idle Shutdown Timer Enabled	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/12/2019 9:38:28 AM
Effective Date: Jan 1, 2019
Prepared by: Administrator

Complete

Model Number: Model 520
Quote/DTPO/CO: Q64227141
Version Number: 38.10



Data	Code	Description	\$ List	Weight
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372	O	Eff EIST NA Expiration Miles	0	0
2091640	O	Effective VSL Setting NA	0	0
2140150	O	Remote PTO And Throttle Provision	37	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed	0	0
2521090	O	Immersion Type Block Heater 110-120V Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	74	2
2522050	U	PACCAR STARTER 12V	0	0
2522110	S	PACCAR 12V Starter N/A PACCAR MX Engines	0	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539740	O	Kissling Battery Disconnect Switch 300 AMP; Mounted on battery box	222	3
2621000	S	2-Speed Fan Clutch For Frequent Start/Stops	0	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921110	S	PACCAR Fuel/Water Separator Standard Service Interval	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3010400	O	Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	10	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0	0
3120450	S	Stainless Steel Grille	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/12/2019 9:38:28 AM
Effective Date: Jan 1, 2019
Prepared by: Administrator

Complete

Model Number: Model 520
Quote/DTPO/CO: Q64227141
Version Number: 38.10



Data	Code	Description	\$ List	Weight
3261980	S	Heavy Duty Air Cleaner Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365300	S	Exhaust Vertical LH DPF/SCR LH Back of Cab Vertical (2017).	0	0
3381770	O	Curved Tip Standpipe(s)	70	1
3387870	S	24in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)	0	0
Transmission & Equipment				
4052110	S	Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.03)	0	0
4210200	O	1760 HD Driveline, 1 Midship Bearing	220	-15
4250490	U	ALLISON 5TH GEN RDS, PKG 170	0	0
4252330	U	ALLISON SHIFT SELECT TRANSITION INPUT D	0	0
4252830	O	Allison FuelSense 2.0 Basic Features include: EcoCal shift technology keeps the engine speed at the most efficient level and DynActive Shifting system incorporates a learning algorithm that selects variable shift points to find the ideal balance of fuel economy and performance, based upon the vehicle specifications and environmental parameters. This is valuable for applications with heavy start-stop needs like refuse, city delivery, and construction.	-38	0
4252950	O	Omit Allison Neutral At Stop	0	0
4256020	S	Console Mounted Push Button Shifter Allison transmissions	0	0
4256350	O	Allison RDS Auto Neutral AK Single steer LH or RH. Add Code 4540940 if plumbed to flip valve to actuate service brakes is desired.	298	0
4256640	O	Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/12/2019 9:38:28 AM
Effective Date: Jan 1, 2019
Prepared by: Administrator

Complete

Model Number: Model 520
Quote/DTPO/CO: Q64227141
Version Number: 38.10



Data	Code	Description	\$ List	Weight
4256870	O	Allison Output Function S Neutral Indicator For PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in Neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is switched On. Also, with this configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral.	0	0

Air & Trailer Equipment

4510330	S	Bendix AD-IS EP Air Dryer with Heater And Coalescing Filter; Extended Purge	0	0
4520420	O	Pull Cords All Air Tanks	10	1
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4543470	U	INSTALL FRAME MOUNTED AIR TANKS AS FAR	427	0
4612000	O	Route Air & Electric Lines To Allow Welding of sub frame to top of frame 8in forward of BOC to EOF	451	0

Tires & Wheels

5069700	U	FF: BR 20PLY 315/80R22.5 M843 MSI	0	0
5069880	O	FF: BR 20ply 315/80R22.5 R249	40	-24
5169430	O	RR: BR 14ply 11R22.5 M710 Ecopia Diameter = 41.8 inches; SLR = 19.5 inches	88	56
5190008	O	Code-rear Tire Qty 08	0	0
5220530	O	FF: Alcoa 89U647 22.5X9.00 Clean Buff Finish Aluminum, Ultra ONE wheels with MagnaForce alloy.	336	-94
5310600	S	RR: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, Two Hand Holes	0	0
5390008	O	Code-rear Rim Qty 08	0	0

Fuel Tanks

5556190	O	26in Aluminum 100 Gallon Fuel Tank LH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	621	18
5604100	O	Location LH BOC 100 Gallon	0	0
5650490	S	Fuel Cooler Required with single fuel tank.	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/12/2019 9:38:28 AM
Effective Date: Jan 1, 2019
Prepared by: Administrator

Complete

Model Number: Model 520
Quote/DTPO/CO: Q64227141
Version Number: 38.10



Data	Code	Description	\$ List	Weight
5651390	O	Top Of Fuel Tank 5 in Below Top Of Frame	589	33
5652890	O	DEF Tank Mounted LH BOC Models 220 and 520 mounted LH cab fender N56500 MOUNT DEF TANK BACK N56510 AS FAR AS POSSIBLE	0	0
5652990	O	Standard DEF To Fuel Ratio 2:1 Or Greater	0	0
5655069	S	DEF Tank 520	0	0

Battery Box & Bumper

6011070	O	Aluminum Battery Box LH Frame Mtd Back Of Fender 8 inch below top of frame	366	0
6122810	O	Steel Bumper Swept Back Painted Requires bumper extension, includes 2front tow eyes with pins	-149	2
6132400	O	Notched Top Flange Of Bumper	50	0
6132420	O	4-7/8 in Bumper Extension, Without FEPTO	416	31

Cab & Equipment

6501090	O	53in LCF ProBilt Cab RH Drive Use with auto trans. Includes steel frames with alum and fiberglass panels, all alum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, full insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, pull down windshield sunshade, 16in steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC controls, rear cab corner windows, 18in bolt-on step on each side, self-canceling turn signals and Front Directional and Side Mounted Turn Signals.	1,339	0
6800500	S	4.5 Inch Rubber Flares on Cab and Wheel Well Fenders	0	0
6911720	S	Peterbilt Driver Seat	0	0
6921720	S	Peterbilt Passenger Seat	0	0
6931120	O	Seat Belt Color Orange IPO Standard Black	10	0
6939400	O	Air Ride Driver	310	43
6939440	S	Low Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939500	O	Air Ride Passenger	310	43
6939540	S	Low Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/12/2019 9:38:28 AM
Effective Date: Jan 1, 2019
Prepared by: Administrator

Complete

Model Number: Model 520
Quote/DTPO/CO: Q64227141
Version Number: 38.10



Data	Code	Description	\$ List	Weight
7000000	S	Gray Interior Color Includes ABS gray headliner & rear cab panel, gray vinyl engine tunnel cover. For LH, RH, and dual steer dual seated power windows are standard on both doors. For dual steer RH stand-up the LH window is power and the RH window is a manual sliding window.	0	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7001620	S	Steering Wheel with Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7220130	S	Rear Window Back of Cab Standard Tint 18.5in X 54in	0	0
7230350	S	Two Piece Flat Windshield	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7561260	S	Black LH/RH Tri-plane Mirrors, Heated, Motorized, Mounted to Doors. Features: Heated on All Three Surfaces, Upper/Lower Mirrors are Convex and Middle is a Flat Pane Motorized Mirror. Right Click on Option and Select Picture to See a Picture of the Mirror.	0	0
7610020	S	(1) Air Horn 15in Painted Mounted under cab.	0	0
7725715	O	ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3.	388	10
7725740	O	Midlevel Speaker Package For Cab (4) Speakers	134	6
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilt's proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesn't require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. SmartLINQ is standard with MX-13 engines and available on the models 587,579,567,389,367 and 365.	0	0
7851330	O	Cab Tilt Pump Air Assist	509	0
7851870	O	Rain Gutters Over Driver and Passenger Doors	74	8
7852150	S	Peterbilt Pantograph Windshield Wipers With intermittent feature.	0	0
7900090	O	Triangle Reflector Kit Shipped Loose	20	13

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	2/12/2019 9:38:28 AM	Complete	Model Number:	Model 520
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q64227141
Prepared by:	Administrator		Version Number:	38.10



Data	Code	Description	\$ List	Weight
7900970	S	Backup Alarm Wiring To EOF	0	0
8011400	S	Main Transmission Oil Temperature Gauge Located in Driver Information Display	0	0
8021315	S	Air Restriction Indicator Mounted on Exhaust Stanchion	0	0
8031120	O	Warning Light Battery Disconnect, Switch Engaged (Marker light) external mounted.	15	0
8071025	O	Manifold Pressure Gauge Located in Driver Information Display	0	0
8110090	S	Headlights Single Rectangular Halogen	0	0
8120550	O	(5) Light Guards On Marker Lights	20	2
8120570	S	(5) LED Clearance With (2) LED Marker Lights Includes (5) lights mounted on roof of cab and (1) cab side marker light mounted in front of each cab door.	0	0
8133900	S	None Furnished Stop/Tail/Backup Lights Available with Full Truck only. Not available with Tractor.	0	0
8133960	O	Daytime Running Lights Required on all Canadian vehicles	60	0

Paint

8500710	O	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85200 FRAME L0001EA BLACK N85700 BUMPER L0001EA BLACK	0	0

Shipping Destination

8999990	O	Shipping Destination Other Than Dealer (Specify by narrative) N89900 GS Products N89910 322 Lavansville Rd N89920 Somerset, PA 15501 N89930 Russ Palmer 814-445-5866	0	0
---------	---	--	---	---

Options Not Subject To Discount

9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9400094	S	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	0
9408982	O	Vehicle Layout Option is not subject to discount. Fleets will be split prior to build so that the charge is applied to only one unit. Quotes will not reflect this. N94000 GS PRODUCTS SOMERSET, PA 15501 N94010 RUSSPALMER@G-SPRODUCTS.COM	1,350	0

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 2/12/2019 9:38:28 AM
Effective Date: Jan 1, 2019
Prepared by: Administrator

Complete

Model Number: Model 520
Quote/DTPO/CO: Q64227141
Version Number: 38.10